MATERIAL SAFETY DATA SHEET

DOUCT NAME: DESIGN MAST PETAL PROOFER 728 HMIS CODES: H F R P

..ODUCT CODE: L-10569

CODES H F K

1 4 0

MANUFACTURER'S NAME: HYDROSOL INC. ADDRESS: 455 FRONTAGE ROAD, BURR RIDGE, IL 60521

EMERGENCY PHONE: 312-598-5448 INFORMATION

DATE PREPARED : 08-18-87

INFORMATION PHONE: 312-598-5448

NAME OF PREPARER : ESP

REASON REVISED : UPDATE

-(-i-

====== SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION =======

HAZARDOUS COMPONENTS	යා ම ම ම ම ව සා දා සා සා සා සා සා සා සා සා	CAS NUMBER		TIONAL EXPOSURE LIMITS ACGIH TLV	VAPOR PRE		WEIGHT PERCENT
2-PROPANOL, ISOPROPYL ALCOHOL PROPYLENE SLYCOL METHYL ETHER 2-BUTOXYETHANOL, GLYCOL ETHER EB ISOBUTYL ACETATE	v	67-63-0 107-98-2 111-76-2 110-19-0	400 NE 50 200	400 NE 25 150	33.0 8.4 0.6 13.0	68F 68F 68F 68F	< 5.0% 5 < 5.0%
ACETONE BUTANE PROPANE		67-64-1 106-97-8 74-98-6	1000 1000 1000	750 NE ASPHYXIANT	181.0 1640.0 6350.0	68F 68F 68F	45 10 15

========= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING POINT: NOT APPLICABLE

SPECIFIC GRAVITY (H2O=1): 0.7

VAPOR DENSITY: N/A EVAPORATION RATE: N/A

V.O.C.: N/A

SOLUBILITY IN WATER: SLIGHT TO MODERATE APPEARANCE AND ODOR: AEROSOL PRODUCT

========== SECTION IV - FIRE AND EXPLOSION HAZARD DATA ============

FLASH POINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1% UPPER: 13.0%

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EX-POSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT. OBTAIN MEDICAL ATTENTION.

= SECTION V - REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID

APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)

STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE FUNES WHEN HEATED TO DECOMPOSITION. FUNES MAY CONTAIN CARBON MONOXIDE AND OXIDES OF NITROSEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RESPIRATORY IRRITATION, DIZZINESS, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION, EYE WATERING.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITION.

EYES: LIQUID OR VAPOR CAN IRRITATE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN BE ABSORBED THROUGH SKIN. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING SKIN TO CRACK, LEADING TO DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: EYE, SKIN, AND RESPIRATORY SYSTEM IRRITANT. NARCOTIC IN HIGH CONCENTRATIONS. SEVERE OVEREXPOSURE MAY CAUSE DAMAGE TO THE BLOOD.

CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERV-OUS SYSTEM AND OTHER INTERNAL ORGAN DAMAGE.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

LIVER AND KIDNEY DISEASE, ANEMIA, CORONARY DISEASE. PREGNANT WOMEN SHOULD AVOID EXPOSURE TO SOLVENTS.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION.

SKIN: REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

ŧ	-	4	n	=	۷	O
1	-	Ł	u		0	7

an links

MATERIAL SAFETY DATA SHEET

PAGE 3 OF 3

within come which which wide speed make that when their	SECTION	VII	-	PRECAUTIONS	FOR	SAFE	HANDLING	AND	LISE

EPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

HAVID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DO NOT TAKE INTERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

OTHER PRECAUTIONS

SMALL PRESSURIZED CONTAINERS OF FLAMMABLE PRODUCTS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTIBLES WITH RESPECT TO CONSTRUCTION, DRAINAGE, CONTROL OF IGNITION SOURCES, AND VENTILATION EXCEPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS.

	SECTION VIII	4000	CONTROL	MEASURES	=======================================
--	--------------	------	---------	----------	---

RESPIRATORY PROTECTION

TUNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO LIMITS A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES

NONE UNDER NORMAL USE. SOLVENT RESISTANT GLOVES REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE INFORMATION CONTAINED
REMEIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, HYDROSOL, INC. ASSUMES NO RESPONSIBILITY FOR ITS USE.

		•	Find , to etg.