

Material Safety Data Sheet

Section 1 – Identification

Product Name: Fleck's Cement Powder

FLECK'S CEMENT POWDER

Manufacturer: Mizzy Inc. A division of Keystone Industries

52 W King St.

Information Contacts: (800)-333-3131

Myerstown, PA 17067

Emergency Phone Numbers: US & Canada 1 (800)-535-5053

Chemical Name: N/A Product Use: Dental Cements

Product #: Various Section 2 – Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May cause allergic skin reaction
- May cause eye irritation
- Dust may cause irritation to nose, throat, and lungs, which will disappear in 24 hours
- This product may contain particulate, not otherwise classified (Nuisance Dust).

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	Inhalation, skin, and ingestion.
Eye	May cause eye irritation
Skin	Repeated or prolonged exposure may cause allergic skin rashes.
Ingestion	Higher concentration can irritate respiratory system
Inhalation	Inhalation of high levels of cement may result in tightness of chest, metallic taste, coughing, dizziness,
	fever, chills, headache, nausea, and dry throat. Over exposure may produce symptoms known as metal
	fume fever or (zinc shakes); an acute, self limiting condition without recognized complications.
	Symptoms of metal fume fever include chills, fever, muscular pain, nausea, and vomiting. Like any
	finely divided particulate matter, cement may cause mechanical irritation to skin and eyes.
Sub-Chronic Effects	Chronic exposure to cement may cause respiratory tract irritation with nasopharyngities and laryngitis.

NOTE: Refer to Section 11, Toxicological Information for Details Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH	Carcinogen	%
•				TWA/STEL	TWA/STEL	IARC/NTP/OSH A	
Zinc Oxide	1314-13-2	215-222-5	Zinc Oxide	TWA = 15 mg / m^3	N/E	Not Listed	>90
Magnesium Oxide	1309-48-4	215-171-9	Magnesium Oxide	TWA = 15 mg / m^3	$TWA = 10 mg / m^3$	Not Listed	<10

 N/E - None
 N/DA - No Data Available

 Established
 N/A - Not Applicable

 N/R - Not Reviewed
 N/A - Not Applicable

(items in parenthesis relate to 1999/45/EC)

 Zinc Oxide:
 Danger Symbol – GHS09 (N)
 Hazard Statement:
 H400 (R50/53)

 Magnesium Oxide:
 Danger Symbol – N/E

Precautionary Statement: P501 (S60), P273 (S61)

See Section 16 for Hazard and Precautionary Statement Key.

Section 4 – First Aid Measures

First Aid for Eye	Immediately flush eyes with plenty of water for at least 15 min. occasionally lifting the upper and
	lower lids. Get medical help if discomfort persists.
First Aid for Skin	Immediately flush skin with plenty of soap and water for at least 15 min. while removing contaminated clothing and shoes. Get medical help if discomfort persists.
First Aid for Ingestion	Remove to fresh air. Get medical help if discomfort persists.

Date of Issue: 03/26/2014

~Verified on 2014-09 by Henry Schein to be the most current version of the SDS. To be verified again on 2017-09. ~



Material Safety Data Sheet FLECK'S CEMENT POWDER

First Aid for Inhalation Remove from exposure to fresh air immediately. Get medical help if discomfort persists.

Section 5 – Fire Fighting Measures Flash Point (°F/°C) Flammable Limit (vol%) Auto-ignition Temperature (vol%) N/A N/A N/A Method: Extinguishing Media: In case of fire use water spray, dry chemical, carbon dioxide or foam. Non-combustible Fire Fighting Instructions: Unusual Hazards: Substance is noncombustible. Section 6 – Accidental Release Measures Spill or Release Shovel or vacuum up spilled product and place in closed container for disposal. Do not flush into sewer, stream, or other bodies of water or soil. Procedures Section 7 – Handling and Storage Handling Limit all unnecessary personal contact. Use appropriate PPE when handling. Storage Store in a cool, dry place. **Explosion Hazard** None. Section 8 – Exposure Controls / Personal Protection Mechanical ventilation preferred to keep dust levels down. Engineering Controls **Personal Protective Equipment** General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Use safety eyewear for protection against airborne particulate. Eye/ Face Protection Skin Protection Use impermeable clothing to prevent any contact with this product, such as gloves, apron, boots, or whole body suit. Prevents skin irritation in hypersensitive individuals.

Respiratory In case of insufficient ventilation or extremely dusty environments, wear suitable respiratory equipment. Protection

Section 9 – Physical and Chemical Properties

11		dor Threshold None	PH N/A		ific Gravity O = 1): 5.7- 5.9	Viscosity N/A		olatile I/A	
Boiling Point/ Freezing Point	Decomposit Temperatu		Octanol/Water titioning Coefficie Log Po/w		Vapor essure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/DA		N/DA		N/A	N/A	N/A	N/A	N/A
Flash	Point (°F/°C))	Flamma	ble Lin	nit (vol%))	Auto-ignition T	emperature	e (vol%)
N/A			N/A]	N/A		

Section 10 – Stability and Reactivity

Stability:	Incompatibility (Materials to Avoid):		
Stable	Acids		
Hazardous Decomposition Products:	Hazardous Polymerization:		
None Will not occur			
Conditions to Avoid: Exposure to moisture or water.			



FLECK'S CEMENT POWDER

Section 11 – Toxicological Information

Material Safety Data Sheet

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irr	itation – skin	Irritation – Eye
N/DA	N/DA	N/DA	N/DA		N/ DA
Sensitization		Mutagenicity		Sub-ch	ronic Toxicity
N/ DA		N/DA			N/ DA

Section 12 – Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/ DA	N/ DA	N/ DA	N/ DA

Chemical Fate Information

Chemical Oxygen Demand N/ DA	Biodegradability	N/DA. This material is not expected to bioaccumulate.
	Chemical Oxygen Demand	N/ DA

Section 13 – Disposal Considerations

Dispose of in compliance with governmental regulation (state and federal).

Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14 – Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-regulated
Identification Number:	N/A
Marine Pollutant:	N/A
Special Provisions:	N/A
Emergency Response Guidebook (ERG) #:	
IATA (DGR):	
Proper Shipping Name:	UN3077, Environmentally Hazardous Substance, Solid, N.O.S. (Zinc Oxide), 9, III
Class or Division:	9
UN or ID Number:	UN3077
Packaging Instructions:	III
Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	UN3077, Environmentally Hazardous Substance, Solid, N.O.S. (Zinc Oxide), 9, III
Class or Division:	9
UN or ID Number:	UN3077
Special Provisions & Stowage/Segregation:	N/A
Emergency Schedule (EmS)#:	N/A
Other Information:	N/A

Section 15 – Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following HAP's or ODS:
	• NONE
Clean Water Act: Priority	This product contains the following chemicals listed under the U.S. Clean Water Act
Pollutant	Priority Pollutant and Hazardous Substance List:
	• None
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other
	applications as an indirect food-packaging additive.



Material Safety Data Sheet

FLECK'S CEMENT POWDER

Occupational Safety and Health	This product is considered to be hazardous under the OSHA Hazard Communication
Act	Standard. It's hazards are:
	• Zinc Oxide – CAS # 1314-13-2 (Acute health hazard)
	• Magnesium Oxide – CAS # 1309-48-4 (Acute health hazard)
RCRA	This product contains the following chemicals considered to be hazardous waste under
	RCRA (40 CFR 261).
	• None
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous
	substances.
SARA Title III: Section 302	This product contains chemicals regulated under Section 304 as extremely hazardous
(TPQ)	chemicals for emergency release notification ("CERCLA" List):
	• None
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication
	Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are:
	• Zinc Oxide – CAS # 1314-13-2 (Acute health hazard)
	• Magnesium Oxide – CAS # 1309-48-4 (Acute health hazard)
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting
	requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization
	Act of 1986 and 40 CFR Part 372: None
TSCA Section 8(b): Inventory:	This product does contain chemicals listed on the TSCA inventory or otherwise complies
	with TSCA pre-manufacture notification requirements.
TSCA Significant New Use Rule:	• Magnesium Oxide – CAS # 1309-48-4
	• Zinc Oxide – CAS # 1314-13-2
	None of the chemicals in this material have a SNUR under TSCA.

State Regulations

State Regulations	
CA Right-to-Know Law:	Magnesium Oxide – CAS # 1309-48-4
California No Significant Risk	Zinc Oxide – CAS # 1314-13-2
Rule:	None
MA Right-to-Know Law:	Magnesium Oxide – CAS # 1309-48-4
6	Zinc Oxide – CAS # 1314-13-2
NJ Right-to-Know Law:	Magnesium Oxide – CAS # 1309-48-4
	Zinc Oxide – CAS # 1314-13-2
PA Right-to-Know Law:	Magnesium Oxide – CAS # 1309-48-4
	Zinc Oxide – CAS # 1314-13-2
FL Right-to-Know Law:	
MN Right-to-Know Law:	Magnesium Oxide – CAS # 1309-48-4
-	Zinc Oxide – CAS # 1314-13-2

International Regulations

CDSL: Canadian Inventory	Magnesium Oxide – CAS # 1309-48-4
(on Canadian Transitional List)	Zinc Oxide – CAS # 1314-13-2

Labeling according to EC directives - 1272/2008 {CLP} and 1999/45/EC (items in parenthesis relate to 1999/45/EC)

European Community:	For Fleck's Cement Powder (finished product):
	 DANGER SYMBOLS: GHS07 (Xi) – Irritant. GHS09 (N) – Dangerous to the environment HAZARD STATEMENT: H317 (R43), H320 (N/A), H400 (R50), H335 (R37) PRECAUTIONARY STATEMENT: P102 (S2), Keep out of reach of children. P261 (S24), Avoid breathing dust/fume/gas mist/vapor sprays. P280 (S36/37/39), Wear protective gloves/clothing/eye protection/face protection. P309+314 (S45), If exposed or you feel unwell, get medical advice/attention. P273 (S61).



Material Safety Data Sheet

FLECK'S CEMENT POWDER

Section 16 – Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

(items in parenthesis relate to 1999/45/EC)

Danger Symbols:

GHS09 (N) – Dangerous to the Environment. GHS07 (Xi) – Warning (Irritants)


Hazard Statement:

H400 (R50/53), Very toxic to Marine life, may cause long term effects. H317 (R43), May cause allergic skin reaction. H320 (N/A), Causes eye irritation. H335 (R37), May cause respiratory irritation.

Precautionary Statement:

P102 (S2), Keep out of reach of children. P260 (S23), Do not breathe dust/fume/gas/mist/vapors/spray. P261 (S24), Avoid breathing dust/fume/gas mist/vapor sprays. P280 (S36/37/39), Wear protective gloves/clothing/eye protection/face protection. P309+314 (S45), If exposed or you feel unwell, get medical advice/attention. P305+334 (S26), In case of contact with eyes, rinse immediately with water. P301+315 (S46), If swallowed, get immediate medical advice / attention. P405 (S1), Keep locked up. P501 (S60), Dispose of properly. P273 (S61), Avoid release into environment.

Hazard Rating System (Pictograms)



MSDS Prepared by:	WME	
Revision History:	03/04/2011	Replaces prior MSDS - Completely revised.
	03/26/2014	Reviewed, No Changes

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable.

Keystone Industries components are provided on an as is basis without warranties of any kind either expressed or implied. Keystone Industries does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said Keystone Industries components.