# 80-771

# DURA-PLEX HI PERFORMANCE CHAIN & CABLE LUBE

HMIS RATING		NFPA 704 RATING
Health 2	MATERIAL	Health 2
Flammability 4	SAFETY DATA	Flammability 4
Reactivity 0	SHEET	Reactivity 0
KIMBALL-MIDWEST	1	NFPA 30B LEVEL
P.O. BOX 2470		N/A
COLUMBUS, OH 43216-		11/74
CORPORATE TELEPHON EMERGENCY TELEPHON		
1	PRODUCT IDENTIFICAT	ION
PART NUMBER		
PRODUCT NAME	DURA-PLEX Hi-Perfor	mance Chain & Cable
CHEMICAL FAMILY	Lube	
	N/A Consumer Commodi	ty ORM-D
2	HAZARDOUS INGREDIE	NITS
SPECIFIC CHEMICAL IDENTITY, CO		ACGIH TLV STEL %
*n-Hexane (64742-49-0)	50ppm	50ppm <30
Olefin Polymer (Proprietary) Propane/Isobutane/N-Butane	5	5mg/m <sup>3</sup> 10mg/m <sup>3</sup> <30 800ppm - <25
Proparie/isobularie/is-bularie	2 (00470-00-0) 000ppin	800ppin - <25
	dwithanasterisk(*)aretoxicchemicalssubj Imentsand Reauthorization Act (SARA) of	
notifyeachpersontowhomthis	mixture of tradename product is sold. This st	atementmustnotbedetached.Any
copy or redistribution of this	Material Safety Data Sheet shall include	this statement. **Ceiling
	3. PHYSICAL DATA	
BOILING POINT (RANGE).	43 - 1	159°F
-	70°FN/A	
, ,	)>1 Neglio	aibla
	= 1) 0.691	
	νΤΝ/Α	
	6=1)<1 	06
	RDark (	
		nt odor
4.	FIRE AND EXPLOSION D	ATA
	-141°l	
	(%)	
LOWER EXPLOSIVE LIMIT	(%)1.0	
EXTINGUISHING MEDIA		
	chem ROCEDURESConta	ical, Water fog .
SI ECINETINEI IOITINGT	if exposed to heat (fire).	As in any fire, wear self
	contained breathing app (MSHA/NIOSH) and full prot	
FIRE AND EXPLOSION HA	ZARDS Vapor	rs can travel to a sources
	of ignition and flash back. product residue (liquid a	
	dangerous. Do not pre	ssurize, cut, weld, braze
	solder, drill, grind, or expo flamer sparks, static elect	
	ignition; they may explode	
	Empty drums should be	
	and promptly returned to promptly disposed of.	a urum reconditioner, o
	5. HEALTH EFFECTS DAT	Δ
	SHORT TERM EFFECTS OF EXPOSU	
ROUTE OF ENTRY	SHORT TERM EFFECTS OF EXPOSE	

SHORT TERM EFFECTS OF EXPOSORE		
ROUTE OF ENTRY	Skin Contact, Skin Absorption, Inhalation, Ingestion and Eye Contact.	
HEALTH HAZARDS		
(ACUTE AND CHRONIC)	Overexposure may cause nervous system damage, lung damage and kidney damage.	
EYE CONTACT	lrritation causes pain, tearing, reddening and swelling accompanied by stinging sensation.	
SKIN CONTACT	Prolonged or repeated contact could cause defattting and drying of skin. Irritation to skin and dermatitis.	
INGESTION	Harmful or fatal if swallowed. Corrosive and may cause severe & permanent damage to mouth, throat and stomach.	
INHALATION	Jeadaches, dizziness, nausea, decrease blood pressure, changes in heart rate and cyanosis may result from overexposure.	

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE .....None Listed

5. HEALTH EFFECTS DATA CON'T		
EYE CONTACT	FIRST AID PROCEDURES	
ETE CONTACT	Hold eyelids apart and immediately flush eyes with plenty of water. Get medical attention, if irritation persists.	
SKIN CONTACT	Immediately flush skin with plenty of water. Remove Clothing. Get medical attention immediately. Wash	

	clothing separately before reuse.
INGESTION	Get medical attention immediately. If swallowed, DO NOT INDUCE VOMITING unless directed to do so by medical personnel. Never give anything by mouth to an unconscious victim or a person losing consciousness.
INHALATION	Remove the person away from exposure to fresh air. If not breathing give artificial respiration. If have trouble breathing, give oxygen. Get immediate medical attention.

#### SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines) ...... Not presently on any lists.

6. REACTIVITY		
STABILITY	Stable	
INCOMPATIBILITIES	Strong acids, alkalis, oxidizers and amines. All sources of ignition, welding arcs and open flames.	
HAZARDOUS DECOMPOSITION		
PRODUCTS	Oxides of carbon, nitrogen.	
HAZARDOUS POLYMERIZATION	Will not occur under normal conditions.	
HAZARDOUS POLYMERIZATION CONDITIONS	None known.	

### 7. PRECAUTIONS FOR SAFE HANDLING & USE

PROTECTIVE EQUIPMENT	
REQUIREMENTS	Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during use. NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge. Where contact is expected wear chemical resistant gloves, a chemical suit, rubber boot, and chemical safety goggles and plus face shield.
WASH REQUIREMENTS	Wash with soap and water.
SPILL OR LEAK PROCEDURES .	Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container.
WASTE DISPOSAL METHODS	Dispose of in accordance with local, state, and federal regulations.
HANDLING & STORAGE	Wash thoroughly after handling. Do not allow to freeze. Avoid temperatures above 120°F
OTHER PRECAUTIONS	Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of vapors; protection provided by air purifying respirators is limited.

### 8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.

