MATERIAL SAFETY DATA SHEET Vaivoiine

1 C. BOM 14001 LEXINGTON, KENTUCKY 40512 1506-264-7000 Emergency Telephone 1 (800) 274-5263 or 1-803-ASHLAND

000551

CARQ AP TRAC FL

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: CARQ AP TRAC FL

B.W.P. DISTRIBUTORS INC.
B.W.P. DISTRIBUTORS INC
TECHNOLOG PARK
CARQUEST CORPORATION
1055 BRONX RIVER AVE
BRONX NY 10472

08 70 000 0813563-090

Data Sheet No: 0173402-003 Prepared: 04/20/89 Supersedes: 01/26/88

PRODUCT: 62018000 INVOICE: 071903 INVOICE DATE: 07/06/90

70 HORIZON DRIVE

ATTN: PLANT MGR / SAFETY DIR.

SECTION SI-PRODUCT ADDENTA FACATION

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

DOT Hazard Classification: NOT APPLICABLE

NEW YORK OF THE PROPERTY OF THE SECULION STITLE COMPONENTS AND THE PROPERTY OF THE PROPERTY OF

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION.

SEE DEFINITION PAGE FOR CLARIFICATION

 INGREDIENT
 % (bv WT)
 PEL
 TLV
 Note

 HYDRAULIC OIL ADDITIVE
 5-10
 (1)

 PETROLEUM OIL
 70-85
 5 MG/M3
 5 MG/M3
 (2)

Notes:

- (1) THIS PROPRIETARY MIXTURE CONTAINS 20% ZINC COMPOUNDS. ZINC COMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III.
- (2) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM.

Boiling Point	UNAVAILABLE	LODATA System with the section of th
Vapor Pressure	NOT APPLICABLE	
Specific Vapor Density		HEAVIER THAN AIR
Specific Gravity		.876
Percent Volatiles	NOT APPLICABLE	
Evaporation Rate		SLOWER THAN ETHER
Appearance of the second secon		NOT SPECIFIED
State		LIQUID
Form		HOMOG SOLN

MARKET THE PROPERTY OF A SECRETARION ALLY FILE CAND MEXPLED STOOM AND THE PROPERTY OF THE PROP

FLASH POINT

400.0 Deg F

204.4 Deg C)

EXPLOSIVE LIMIT

UNAVAILABLE

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES:

HEALTH- 1

FLAMMABILITY- 1

REACTIVITY- 0

SECTION SYCHEADITH CONTROL OF THE SECTION SYCHEADITH CHAZARD COATA CONTROL OF THE SECTION OF THE

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.

EFFECTS OF ACUTE OVEREXPOSURE: FOR COMPONENT

TOXICOLOGICAL TESTING INDICATES THAT SIMILIAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR 1910.1200).

COPYRIGHT 1989

CONTINUED ON PAGE: 2

MATERIAL SAFETY DATA SHEET Vaivoline

P. C. EOM 14007 LEXINGTON, KENTUCKY 40512 (605) 264-7000

Emergency Telephono 1 (800) 274-5263 or 1-800-ASHLAND

000551

CARQ AP TRAC FL

Page: 2

是表现的一种文化是基础的是CASEDTION IN-HEALITH WHAZARD WDATA 中COontinued)一件中央系统中国中国的企业

FIRST AID:

IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.

IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

IF SHALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON HARM AND QUIET, AND GET MEDICAL ATTENTION.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

SECTION WI-REACTIVITY DATA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH:, STRONG OXIDIZING AGENTS.

THE HARD SECTION AVIOLES PILL OR ALSEAK SPROCEDURES AND ADMINISTRATION OF THE PROCEDURES AND ADMINISTRATION OF THE PROCEDURE ADMINISTRATION OF THE PROCEDURE AND ADMINISTRATION OF THE PROCEDURE ADMINISTRATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

LARGE SPILL: PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED.

PERSONS NOT MEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

MASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

DESTROY BY LIQUID INCINERATION.

RESPIRATORY PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

VENTILATION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

PROTECTIVE GLOVES: NOT NORMALLY REQUIRED.

EYE PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

TO THE RECOGNICION AND ASPECTAL APPRECAUTIONS AND ADVITED AND APPRECAUTIONS AND ADVITED AND ADDITIONS AND ADVITED ADVITED ADVITED AND ADVITED ADVITED

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

TOXICOLOGICAL TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA 29 CFR 1910.1200 OR FHSA 16 CFR 1500.

HANDLING & STORAGE:

DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR MORE DETAILED INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS. 24-HOUR EMERGENCY NUMBER 1-800-ASHLAND.

FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

CHRONIC INFORMATION:

CONTAINS: PETROLEUM OIL

*** COMPONENTS APPEAR IN SECTION II ***