MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DESIGN MASTER HOLIDAY SNOW 830 HMIS CODES: H F R P

4 / /

IDUCT CODE: L-10616

1 4 0

0.9

MANUFACTURER'S NAME: HYDROSOL INC.

ADDRESS: 455 FRONTAGE ROAD, BURR RIDGE, IL 60521

EMERGENCY PHONE: 312-598-5448

INFORMATION PHONE: 312-598-5448

DATE PREPARED : 08-21-87 NAME OF PREPARER : ESP

REASON REVISED : UPDATE

===== SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION =======

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPAT OSHA PEL	IONAL EXPOSURE LIMITS ACGIH TLV	VAPOR PRESSURE mm Hg @ TEMP	
CYCLOHEXANE	110-82-7	300	300	78.0 68F	5
BUTANE	106-97-8	1000	NE	1640.0 68F	5
PROPARE	74-98-6	1000	ASPHYXIANT	6350.0 68F	₹ 5.0%

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING POINT: NOT APPLICABLE

SPECIFIC GRAVITY (H2O=1):

VAPOR DENSITY: N/A EVAPORATION RATE: N/A

V.O.C.: N/A

SOLUBILITY IN WATER: SLIGHT; DISPERSES. APPEARANCE AND ODOR: AEROSOL PRODUCT

FLASH POINT: N/A METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.3% UPPER: 9.5%

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOO

SPECIAL FIREFIGHTING PROCEDURES

WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EX-POSED TO EXTREME HEAT. IF WATER IS USED, FOG MOZZLES PREFERRED. WEAR GOOGLES AND SELF-CONTAINED BREATHING APPARATUS.

U BUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. LI-QUID CONTENT OF CONTAINER WILL NOT SUPPORT COMBUSTION. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT. OBTAIN MEDICAL ATTENTION. STABILITY: STABLE CONDITIONS TO AVOID

APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)

STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION, HEART ARRYTHMIA.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION, EYES: LIQUID OR VAPOR CAN IRRITATE: PROLONGED CONTACT MAY LEAD TO SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NOT EASILY ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING TO DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: EYE IRRITANT. SKIN IRRITANT. NARCOTIC IN HIGH CONCENTRATIONS.

CHRONIC: NOT KNOWN.

PREGNANT WOMEN SHOULD AVOID EXPOSURE TO SOLVENTS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER DXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION.

SKIN: WIPE OFF WITH TOWEL. WASH WITH SDAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. SET MEDICAL ATTENTION. ======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

PS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORDENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DG NOT TAKE INTERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

OTHER PRECAUTIONS

THE STORAGE OF NON-FLAMMABLE PRODUCTS WITH NON-FLAMMABLE OF FLAMMABLE PRESSURIZING AGENT, IN CARTONS, IS THE SAME AS FOR ORDINARY CANNED GOODS IN CARTONS.

PESPIRATORY PROTECTION

E UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CON-TAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES

NONE UNDER NORMAL USE. SOLVENT RESISTANT REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

DISCLAIMER

IS INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED RE-ADING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, HYDROSOL, INC. ASSUMES NO RESPONSIBILITY FOR ITS USE.