## U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## p/n 45-1

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

	************			0, 10177				
MANUFACTURER'S NAME		SECT	TON I		SED 4/89			
BROTHERS RESEARCH CORPORATION	EMERGENCY TELEPHON			E NO.				
ADDRESS (Number, Street, City, State, and ZIP Co. 2245 AIRPARK DRIVE, BURLINGTON,	494	27215		(919) 22	29–6480			
CHEMICAL NAME AND SYNONYMS SURFACTANTS, SOLVENT, AMMONIUM H	NC .	2/215	TRADENA	ME AND SYN				
CHEMICAL FAMILY	IYDR(	OXIDE	DUR.	AGLOSS VO	CONYMS			
FABRIC & VINYL CLEANER			PROPI	RIETARY	_			
SECTION	11 -	HAZAF	RDOUS INGREDIE	NITO				
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV	ALLOYS AND MI		ATINGS		TLV	
PIGMENTS .		(Units)	BASE METAL	- IALLIC CO	ATINGS	%	(Units)	
CATALYST			ALLOYS					
VEHICLE			METALLIC COATINGS	3				
SOLVENTS 2-BUTOXYETHANOL	3	50	FILLER METAL PLUS COATING OR CO	RE FLUX				
ADDITIVES (CAS# 111-76-2 )			OTHERS					
OTHERS AMMONIA CAS#1336-21-6	10 mg	1 137A		~				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES  YLV								
						1 1	(Units)	
NO - Kirker	NO	NE				-		
						+-	-	
	•		,			+		
250	F104							
	1101	V III - P	HYSICAL DATA					
BOILING POINT (°F.)			SPECIFIC GRAVITY (H			1.0		
VAPOR PRESSURE (mm Hg.)	00		PERCENT, VOLATILE BY VOLUME (%)			95		
VAPOR DENSITY (AIR=1)	NA		EVAPORATION RATE				NA	
OLUBILITY IN WATER SOLUBLE								
APPEARANCE AND ODOR WHITE . FOAM,	FRAG	GRANCED						
SECTION IV - I	FIRE	E AND F	XPLOSION HAZAI	8D D 4 T 4				
FLASH POINT (Method used) NON-FLAMMABL			FLAMMABLE LIMIT		Loi		Uel	
EXTINGUISHING MEDIA WATER, CO2, FO								
SPECIAL FIRE FIGHTING PROCEDURES	MI.							
	***************************************	NONE				· · · · · · · · · · · · · · · · · · ·		
UNUSUAL FIRE AND EXPLOSION HAZARDS								
		NONE						

•		SE	CTION	\/	LEAL	TUUAZADDD	A T A		
THRESHOLD LIMIT	VALUE			V .	· ncAi	LTH HAZARD D.	AIA		
EFFECTS OF OVER		NA				?6			
aa.i.a			T BREAT	THE	VAPORS	S FOR EXTENDED	TIME - MAY CAUSE HEADACHE		
OR DIZZINESS.									
EMERGENCY AND F	IRST A	ID PROCEDU	RES						
PROLONGED SKI	V CON	TACT MAY	CAUSE N	1ILI	O IRRI	TATION - AVOID	CONTACT WITH EYES -		
WASH AFFECTED				•					
		•	SECTIO	NC	VI · R	EACTIVITY DAT	ra .		
STABILITY	UNST	ABLE	CONDITIONS TO AVOID						
STAB		LE	Х		OPEN FLAME, EXTREMEM HEAT				
INCOMPATABILITY	(Materia	als to avoid)	NONE	1	OI LIN I	LATE, EXTREMEN	I HEAT		
HAZARDOUS DECO	MPOSIT	10N PRODUC	NAME OF TAXABLE PARTY OF TAXABLE PARTY.						
		MAY OCCUR				CONDITIONS TO A			
HAZARDOUS POLYMERIZATION		WILL NOT OCCUR			v	ODEN TI AM	Type D. Co., May 1		
	1	111661101			<u> </u>	OPEN FLAME,	EXTREME HEAT		
		SECT	ION VI	1 .	SPILL	OR LEAK PROC	EDURES		
STEPS TO BE TAKE	N IN C	•							
LIACII ADEA LITOR	T T T A CTTT	2D OD 0011	on urm	T A T	2000041	M Time Man			
WASH AKEA WIII	1 WATE	ER OR COV	EK WITH	i Al	SORBAN	NT INERT MATERI	AL.		
WASTE DISPOSAL	METHO	0							
				CONTRACTOR OF THE PARTY OF THE					
DISPOSE ACCORI	DING 1	O LOCAL,	STATE	OR	FEDER!	AL REGULATIONS.			
				STATE OF THE PARTY					
		SECTION	VIII .	SPE	CIAL	PROTECTION IN	FORMATION		
RESPIRATORY PRO			unel			: : : : : : : : : : : : : : : : : : : :			
VENTILATION		L EXHAUST	N	IONE			I SPECIAL		
		ANICAL (General)			(		OTHER		
PROTECTIVE GLOV						LEVE ADOTECTION			
NOT REQUIRED EYE PROTECTION						· NOT REQUIRED			
OTHER PROTECTIV	7 E E G U	LWEW I.		NON	(E				
•		<u> </u>	P	4 0 4 4	· ^ ~				
	DG 90					CIAL PRECAUT	IONS		
PRECAUTIONS TO	BE TAK	EN IN HANC	LING AN	D 57	TORING				
DO NOT STORE A		130°F							
OTHER PRECAUTIO	ONS					· ·			

NONE

PAGE (2)