

Pet Butler Air Freshener

MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION OF PRODUCT							
TRADE NAME: Pet Butler Air Freshener CHEMICAL FAMILY: Hydrocarbon Mixture	DATE PREPARED: 07-16-98						
SECTION II - HAZARDOUS INGREDIENTS							
Hazardous Components: OSHA PEL ACGIN TLV OTHER LIMITS % - HYDROTREATED LIGHT PETROLEUM DISTILLATE 64742-47-8 - BUTANE/PROPANE/ISOBUTANE PROPELLENT 1000ppm 800ppm (106-97-8) (74-98-6) (75-28-5)	SECTION 313 - SUPPLIER NOTIFICATION This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning & Community Right to Know ACT of 1986 & of 40 CFR 372: <table border="1"> <thead> <tr> <th>** CAS **</th> <th>Chemical Name</th> <th>% By Weight</th> </tr> </thead> <tbody> <tr> <td>N/A</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table> This information must be included in all MSDS that are copied and distributed for this material.	** CAS **	Chemical Name	% By Weight	N/A	N/A	N/A
** CAS **	Chemical Name	% By Weight					
N/A	N/A	N/A					
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): 0.8 Solubility in Water: NONE Appearance: Clear Liquid Odor: Pleasant Vapor Pressure (mmHg): N.E. Vapor Density (Air=1): N.E. Evaporation RTE (Butyl Act=1): N.E.							
SECTION IV - FIRE AND EXPLOSION HAZARD DATA							
Flash Point: 193 F TCC Extinguishing Media: Regular Foam, CO2, Dry Chemical Special Fire Fighting Procedures: Fire Fighters: Wear self-contained breathing apparatus, cool fire exposed aerosol containers with water spray. Unusual Hazards: Flammable by flame extension test. Contents under pressure. Exposure to temperatures above 120 F may cause bursting.							
SECTION V - REACTIVITY DATA							
Stability: Stable Conditions to Avoid: Extreme Temperatures Polymerization: Will Not Occur Conditions To Avoid: None Incompatible Materials: Strong Acids and Oxidizers Hazardous Decomposition or by-Products: Carbon Dioxide, Carbon Monoxide							
SECTION VI - HEALTH HAZARDS DATA							
Threshold Limit Value: Not Established Carcinogenicity NTP IHRC OSHA: NO NO NO Health Hazards Acute/Chronic: Overexposure by inhalation may cause Irritation, Dizziness, Nausea, Headache, and even Loss of Consciousness. Aspiration may be a hazard. May be harmful or fatal if swallowed. Emergency First Aid Procedures: - Inhalation: Remove to fresh air. If breathing has stopped, administer artificial respiration. Call a Physician. - Ingestion: Do Not induce vomiting. Contact a Physician Immediately. - Eye Contact: Flush eyes immediately with water while removing contaminated clothing and shoes. Wash with plenty of soap and water for 15 minutes.							
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps to be taken							
In case material is released or spilled:	Ventilate area & avoid breathing vapors. Dike & contain spill with inert absorbent material & place in sealed container for disposal.						
Waste disposal method:	Replace cap & discard container in accordance with all approved procedures set forth by Federal, State & Local authorities.						
Precautions to take in handling & storage:	Mop up residue & keep runoffs out of sewer. Keep at room temperature away from direct sunlight.						
Other precautions:	WARNING: Flammable. Contents under pressure. Do Not puncture or incinerate container.						
SECTION VIII - CONTROL MEASURES							
Respiratory Protection: None required with adequate venting Ventilation: Equivalent to outdoors Protective Gloves: Eye Protection: Other Protective Measures: Keep out of reach of children.							
MANUFACTURER: Burning Solutions, Inc. EMERGENCY PHONE: 800-535-5053							
DISCLAIMER: Burning Solutions believes that the information contained on this Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of date of publication, they are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations rules or insurance requirements.							

MATERIAL SAFETY DATA SHEET

N/A = Not Applicable
L-442

(Prepared According to 29 CFR 1910.1200)

Effective Date: 04-01-96

SECTION 1 - PRODUCT IDENTIFICATION			
Product Name:	Pet Butler - Quart	Chemical Family:	DEODORANT
Supplier's Name:	Burning Solutions, Inc.	Proper Shipping Name:	ISOPROPANOL SOLUTION, 3, UN1219,II
Suppliers Address:	1000 Williams Drive Suite 1024 Marietta, GA 30066		HEALTH = 1, FLAMMABILITY = 2, REACTIVITY = 0 PERSONAL PROTECTION = B
SECTION 2 - INGREDIENTS			
CHEMICAL NAME	OSHA/PEL	ACGIH/TLV	CAS NO.
ISOPROPANOL	400 PPM	400 PPM	67-63-0
QUATERNARY AMMONIUM CHLORIDES			5197-80-8
SECTION 3 - PHYSICAL DATA		SECTION 4 - FIRE AND EXPLOSION DATA	
Specific Gravity:	.991	Flash Point (Method Used):	110 F TOC
Solubility in Water:	COMPLETE	Extinguishing Media:	AS REQUIRED BY SURROUNDING FIRE
Physical Description:	CLEAR COLORLESS LIQUID PLEASANT	Special Fire Fighting Procedures:	WEAR SELF-CONTAINED FULL-FACE BREATHING APPARATUS MAY BUILD PRESSURE AND RUPTURE UNDER EXTREME HEAT.
Boiling Point:	> 150 F	Unusual Fire and Explosion Hazards:	IGNITION SOURCE. DO NOT CUT OR WELD ON OR NEAR DRUMS
SECTION 5 - REACTIVITY DATA		SECTION 6 - STORAGE AND HANDLING INFORMATION	
Stability:	STABLE	Precautions to be Taken in Handling and Storage: STORE IN A COOL DRY PLACE AWAY FROM ALL IGNITION SOURCES. KEEP CONTAINER CLOSED WHEN NOT IN USE.	
Conditions to Avoid:	EXTREME TEMPERATURES		
Polymerization:	WILL NOT OCCUR		
Conditions to Avoid:	NONE		
Incompatibility (Materials to Avoid):	STRONG ACIDS AND OXIDIZERS		
Hazardous Decomposition Products:	CO, CO2		
SECTION 7 - HEALTH HAZARDS AND FIRST AID			
Effects of Overexposure: OVEREXPOSURE AND TOXICITY DEPENDS UPON DURATION OF EXPOSURE. SYPTOMS OF OVEREXPOSURE INCLUDE DIZZINESS, NAUSEA, HEADACHE, AND EVEN LOSS OF CONSCIOUSNESS.		First Aid Procedures	
Other Precautions: IGNITABLE MIXTURE		Skin: REMOVE CONTAMINATED CLOTHING AND WASH WITH PLENTRY OF SOAP AND WATER	
Carcinogenicity: NTP: NO IARC: NO OSHA: NO		Eyes: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES LIFTING THE EYELIDS OCCASIONALLY. GET MEDICAL ATTENTION.	
		Inhalation: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION.	
		Ingestion: GIVE SEVERAL GLASSES OF WATER AND INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.	
SECTION 8 - PERSONAL PROTECTION INFORMATION			
Respiratory Protection:	NONE REQ'D W/ ADEQUATE VENTING	Ventilation:	EQUIVALENT TO OUTDOORS
Protective Gloves:	RECOMMENDED	Eye Protection:	RECOMMENDED
Other Protective Equipment: WASH HANDS THOROUGHLY AFTER USE. KEEP OUT OF REACH OF CHILDREN. USE EXPLOSION PROOF MOTOR FOR MECHANICAL VENTING.			
SECTION 9 - SPILL OR LEAK PROCEDURES			
Steps to be Taken in Case Material is Released or Spilled: ELIMINATE ALL IGNITION SOURCES. CONTAIN LARGE SPILLS AND PUMP TO RECOVER. SMALL SPILLS MAY BE MOPPED UP. FLUSH AREA WITH WATER.		Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.	

MANUFACTURER: Burning Solutions, Inc.

Emergency Phone: 800-535-5053

DISCLAIMER: BURNING SOLUTIONS BELIEVES THAT THE INFORMATION CONTAINED ON THIS MATERIAL SAFETY DATA SHEET IS ACCURATE. THE SUGGESTED PROCEDURES ARE BASED ON EXPERIENCE AS OF DATE OF PUBLICATION. THEY ARE NOT NECESSARILY ALL INCLUSIVE NOR FULLY ADEQUATE IN EVERY CIRCUMSTANCE. ALSO, THE SUGGESTIONS SHOULD NOT BE CONFUSED WITH, NOR FOLLOWED IN VIOLATION OF APPLICABLE LAWS, REGULATIONS, RULES OR INSURANCE REQUIREMENTS.