

CCFC1204

|                   |               |         |          |            |   |
|-------------------|---------------|---------|----------|------------|---|
| Post-it® Fax Note | 7671          | Date    | 10/23/00 | # of pages | 2 |
| To                | SHARON LAWREN | From    | Bill C.  |            |   |
| Co.               |               | Co.     | FALCON   |            |   |
| Phone #           |               | Phone # |          |            |   |
| Fax #             | 517 667 3282  | Fax #   |          |            |   |



## MATERIAL SAFETY DATA SHEET

### Anti-Static Color Film Cleaner

**HMIS: 3-0-1-D**

#### SECTION I

Trade Name: Anti-Static Color Film Cleaner  
Chemical Name: Methyl Chloroform with additives  
Manufacturer: Edwal Scientific Products - Division of Falcon Safety Products, Inc.  
Address & Phone #: 25 Chubb Way, Somerville N.J. 08876; (908) 707-4900  
Emergency Phone #: Chemtrec 1-800-424-9300  
Mfg. Model No.: CCFC1204  
FSPID: 0008

#### SECTION II - HAZARDOUS INGREDIENTS

| Ingredients                | CAS #   | %       | TLV | PEL | UNITS |
|----------------------------|---------|---------|-----|-----|-------|
| 1,1,1-Trichloroethane      | 71-55-6 | >95     | 350 | 350 | PPM   |
| Non-Hazardous ingredients* |         | Balance | NA  | NA  | NA    |

\* Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard (29 CFR 1910.1200).

#### SECTION III - PHYSICAL DATA

|                        |                          |                                       |      |
|------------------------|--------------------------|---------------------------------------|------|
| Boiling Point (°F)     | 165.4                    | Specific Gravity (H <sub>2</sub> O=1) | 1.31 |
| Vapor Pressure (MM Hg) | 120                      | Percent Volatile by Vol.              | 100  |
| Vapor Density (Air=1)  | 4.54                     | pH                                    |      |
| Solubility in Water    | insoluble                | Evap Rate (Ether = 1)                 | 0.35 |
| Appearance and Odor    | Clear, Colorless Liquid: | Ether Odor                            |      |

#### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point - None      Flammable Limits      LEL - 8%      UEL - 10.5%  
Extinguishing Media - Carbon Dioxide, dry chemical or foam  
Special Fire Fighting Procedures - Use water spray or fog to cool fire exposed containers  
Unusual Fire & Explosion Hazards - Moderate explosion hazard when exposed to heat and flame

#### SECTION V - HEALTH HAZARD INFORMATION

Symptoms and Effects of Overexposure - Headache, dizziness, fatigue, confusion, central nervous system depression. Prolonged or repeated skin contact may lead to drying, irritation, and dermatitis. Possible skin absorption. Eye irritation.

Medical Conditions Aggravated by Exposure: None known

Falcon Safety Products

Model #CCFC1204

**First Aid**

**Eyes:** Flush eyes with lots of water for at least 15 minutes with eyelids open. Get quick medical attention.

**Skin:** Remove contaminated clothing and wash skin with lots of water. Seek medical attention. Wash clothes.

**Inhalation:** Move victim to fresh air and restore breathing if necessary. Remain with victim until arrival of EMT.

**Indigestion:** Contact local Poison Control Center or physician immediately!

---

**SECTION VI - REACTIVITY DATA**

**Stability** - Normally Stable

**Incompatible Materials** - Avoid Heat, open flame, welding arc, oxidizers, alkalis

**Hazardous Decomposition Products** - Hydrogen Chloride, Carbon Monoxide, Carbon Dioxide, traces of Phosgene and Chlorine

---

**SECTION VII - SPILL or LEAK PROCEDURES**

**Procedures** - Wear personal protective equipment (see section viii). Remove heat and ignition sources; ventilate the area; clean up with inert absorbent.

**Waste Disposal Method** - Dispose of in accordance with Local, State, and Federal Regulations.

---

**SECTION VIII - SPECIAL PROTECTION INFORMATION**

**Respiratory** - If LTV is exceeded, or for symptoms of overexposure, wear a NOSH approved respirator for vapors

**Eyes** - If splash potential exists, wear goggles or face shield

**Inhalation** - Local exhaust may be necessary under some handling/use conditions. Specific needs should be addressed by supervisory or health safety personnel.

---

**SECTION IX - SPECIAL PRECAUTIONS**

Store in a closed container in a well ventilated area. This product does not contain any carcinogens at 0.1% or greater, as defined by IARC, NTP, or OSHA.

**PHYSICIAN** - DO NOT give epinephrine type drugs!

---

**SECTION X - TRANSPORTATION INFORMATION**

**Shipping Information** -

Shipping Containers

DOT

Proper Shipping Name

Consumer Commodity ORM-D

**APPROVAL**

  
Brian P. Billsback

**Vice President of Manufacturing**

Title

**3/23/2000**

Revision Date



history >  
markets >  
company news >  
talk to us >  
Falcon home page <

## Search Results



## MATERIAL SAFETY DATA SHEET

## Anti-Static Color Film Cleaner

HMIS: 3-0-1-D

## SECTION I

Trade Name: Anti-Static Color Film Cleaner

Chemical Name: Methyl Chloroform with additives

Manufacturer: Edwal Scientific Products - Division of Falcon Safety Products, Inc.

Address &amp; Phone #: 25 Chubb Way, Somerville N.J. 08876; (908) 707-4900

Emergency Phone #: Chemtrec 1-800-424-9300

Mfg. Model No.: CCFC1204

FSPID: 0008

## SECTION II - HAZARDOUS INGREDIENTS

| Ingredients                | CAS #   | %       | TLV | PEL | UNITS |
|----------------------------|---------|---------|-----|-----|-------|
| 1,1,1-Trichloroethane      | 71-55-6 | >95     | 350 | 350 | PPM   |
| Non-Hazardous ingredients* |         | Balance | NA  | NA  | NA    |

\* Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard (29 CFR 1910.1200).

## SECTION III - PHYSICAL DATA

|                           |                             |                                          |      |
|---------------------------|-----------------------------|------------------------------------------|------|
| Boiling Point<br>(°F)     | 165.4                       | Specific Gravity<br>(H <sub>2</sub> O=1) | 1.31 |
| Vapor Pressure<br>(MM Hg) | 120                         | Percent Volatile<br>by Vol.              | 100  |
| Vapor Density<br>(Air=1)  | 4.54                        | pH                                       |      |
| Solubility in<br>Water    | insoluble                   | Evap Rate<br>(Ether = 1)                 | 0.35 |
| Appearance and<br>Odor    | Clear, Colorless<br>Liquid: | Ether Odor                               |      |

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

|                       |                     |          |             |
|-----------------------|---------------------|----------|-------------|
| Flash Point -<br>None | Flammable<br>Limits | LEL - 8% | UEL - 10.5% |
|-----------------------|---------------------|----------|-------------|

Extinguishing Media - Carbon Dioxide, dry chemical or foam

Special Fire Fighting Procedures - Use water spray or fog to cool fire exposed containers

Unusual Fire &amp; Explosion Hazards - Moderate explosion hazard when exposed to heat and flame

## SECTION V - HEALTH HAZARD INFORMATION

Symptoms and Effects of Overexposure - Headache, dizziness, fatigue, confusion, central nervous system depression. Prolonged or repeated skin contact may lead to drying, irritation, and dermatitis. Possible skin absorption. Eye irritation.

Medical Conditions Aggravated by Exposure: None known

## First Aid

Eyes: Flush eyes with lots of water for at least 15 minutes with eyelids open. Get quick medical attention.

**Skin:** Remove contaminated clothing and wash skin with lots of water. Seek medical attention. Wash clothes.

**Inhalation:** Move victim to fresh air and restore breathing if necessary. Remain with victim until arrival of EMT.

**Indigestion:** Contact local Poison Control Center or physician immediately!

## SECTION VI - REACTIVITY DATA

**Stability** - Normally Stable

**Incompatible Materials** - Avoid Heat, open flame, welding arc, oxidizers, alkalis

**Hazardous Decomposition Products** - Hydrogen Chloride, Carbon Monoxide, Carbon Dioxide, traces of Phosgene and Chlorine

## SECTION VII - SPILL or LEAK PROCEDURES

**Procedures** - Wear personal protective equipment (see section viii). Remove heat and ignition sources; ventilate the area; clean up with inert absorbent.

**Waste Disposal Method** - Dispose of in accordance with Local, State, and Federal Regulations.

## SECTION VIII - SPECIAL PROTECTION INFORMATION

**Respiratory** - If LTV is exceeded, or for symptoms of overexposure, wear a NIOSH approved respirator for vapors

**Eyes** - If splash potential exists, wear goggles or face shield

**Inhalation** - Local exhaust may be necessary under some handling/use conditions. Specific needs should be addressed by supervisory or health safety personnel.

## SECTION IX - SPECIAL PRECAUTIONS

Store in a closed container in a well ventilated area. This product does not contain any carcinogens at 0.1% or greater, as defined by IARC, NTP, or OSHA.

**PHYSICIAN** - DO NOT give epinephrine type drugs!

## SECTION X - TRANSPORTATION INFORMATION

**Shipping Information** -

Shipping Containers

DOT

Proper Shipping Name Consumer Commodity ORM-D

**PPE-PERSONAL PROTECTIVE EQUIPMENT REQUIRED: NONE**

APPROVAL  President of  
Manufacturing 1/31/2000

Brian P. Billsback Title Revision Date

Please contact Falcon for product status. Some products may be in transition.

[Back to Top](#)

[HOME](#) | [HISTORY](#) | [MARKETS](#) | [COMPANY NEWS](#) | [TALK TO US](#)

© 1999 Falcon Safety Products, Inc.