

3M General Offices  
3M Center  
St. Paul, Minnesota 55144-1000  
(612) 733-1110

02-44  
4752

Duns No.: 00-617-3082

MATERIAL SAFETY  
DATA SHEET



DIVISION: AUTOMOTIVE TRADES DIVISION  
TRADE NAME: 3M BRAND SUPER PANEL FILLER - PART B P/N  
5930  
3M I.D. NUMBER: 60-9800-0661-7  
ISSUED: AUGUST 25, 1987  
SUPERSEDES: JANUARY 10, 1986  
DOCUMENT: 10-2862-0

```
=====
1.  INGREDIENTS                C.A.S. NO.    PERCENT    EXPOSURE
                                                 LIMITS
=====
POLYPROPYLENE GLYCOL          25322-69-4    95.0-100.0  N/D        5
=====
```

SOURCE OF EXPOSURE LIMIT DATA  
1. ACGIH THRESHOLD LIMIT VALUES  
2. FEDERAL OSHA PERMISSIBLE EXPOSURE LIMIT  
3. 3M EXPOSURE GUIDELINES  
4. CHEMICAL MANUFACTURER RECOMMENDED GUIDELINES  
5. NONE ESTABLISHED

ABBREVIATIONS  
N/D - NOT DETERMINED  
N/A - NOT APPLICABLE

```
=====
2.  PHYSICAL DATA
=====
BOILING POINT:      N/D
VAPOR PRESSURE:     N/D
VAPOR DENSITY (AIR=1):  N/D
EVAPORATION RATE ( = 1): N/D
SOLUBILITY IN WATER:  SOLUBLE
SP. GRAVITY (WATER=1): >1
PERCENT VOLATILE:    N/D
VISCOSITY:          APPROX. 600 CPS AT 25 C
pH:                 N/D
APPEARANCE AND ODOR: WHITE LIQUID, SLIGHT ODOR
=====
```

```
=====
3.  FIRE AND EXPLOSION HAZARD DATA
=====
FLASH POINT (CLOSED CUP): 422 F
FLAMMABLE LIMITS - LEL: N/D    UEL: N/D

EXTINGUISHING MEDIA:
CARBON DIOXIDE, WATER FOG, FOAM, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES:
FULL EMERGENCY EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS
SHOULD BE WORN BY FIRE FIGHTERS.
```

**3M General Offices**  
3M Center  
St. Paul, Minnesota 55144-1000  
(612) 733-1110

02-44  
4753

Duns No.: 00-617-3082

MATERIAL SAFETY  
DATA SHEET



MSDS: 3M BRAND SUPER PANEL FILLER - PART B P/N 5930  
AUGUST 25, 1987

Page 2

UNUSUAL FIRE AND EXPLOSION HAZARDS:  
NONE

=====  
4. REACTIVITY DATA  
=====

STABILITY: STABLE

INCOMPATIBILITY - MATERIALS TO AVOID:  
TEMPERATURES GREATER THAN 300 F  
HAZARDOUS POLYMERIZATION: MAY NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:  
NONE

=====  
5. ENVIRONMENTAL INFORMATION  
=====

SPILL RESPONSE:

OBSERVE PRECAUTIONS FROM OTHER SECTIONS. COVER WITH INORGANIC  
ABSORBENT. COLLECT SPILLED MATERIAL, PLACE IN AN APPROVED CONTAINER,  
AND SEAL.

RECOMMENDED DISPOSAL:

INCINERATE IN AN INDUSTRIAL WASTE FACILITY. DISPOSAL ALTERNATIVE:  
MIX WITH PART A, CURE, AND DISPOSE IN A SANITARY LANDFILL. CONSULT  
APPLICABLE REGULATIONS OR AUTHORITIES BEFORE DISPOSAL.

ENVIRONMENTAL DATA:

N/D U.S. EPA HAZARD WASTE NUMBER: N/A REQUIRES HAZARDOUS WASTE  
LABEL AND MANIFEST: NO. EMPTY CONTAINERS SHOULD BE TREATED AS  
HAZARDOUS WASTE: NO.

=====  
6. SUGGESTED FIRST AID  
=====

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST TEN MINUTES.  
IF IRRITATION PERSISTS, CALL A PHYSICIAN.

SKIN CONTACT:

WASH WITH SOAP AND WATER.

INHALATION:

NO ADVERSE HEALTH EFFECTS EXPECTED.

IF SWALLOWED:

INDUCE VOMITING. CALL A PHYSICIAN.

=====  
7. PRECAUTIONARY INFORMATION  
=====

AVOID EYE CONTACT AND PROLONGED SKIN CONTACT.

**3M General Offices**  
3M Center  
St. Paul, Minnesota 55144-1000  
(612) 733-1110

02-44  
4754

Duns No.: 00-617-3082

MATERIAL SAFETY  
DATA SHEET



MSDS: 3M BRAND SUPER PANEL FILLER - PART B P/N 5930  
AUGUST 25, 1987

Page 3

=====  
8. HEALTH HAZARD DATA  
=====

EYE CONTACT: MAY CAUSE MILD IRRITATION ON DIRECT CONTACT.

SKIN CONTACT: PROLONGED AND REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

INHALATION: NO TOXICITY EXPECTED.

INGESTION: MAY CAUSE IRRITATION AND MAY BE HARMFUL IF SWALLOWED.

=====  
The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this Data Sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.  
=====

