

Material Safety Data Sheet

STOR-X GASOLINE STABILIZER

QUICK IDENTIFIER

Common Name: (used on label and list)

K & W STOCK # 2808, 2815, 2832, 2828,
2805 and 2850

May be used to comply with OSHA's Hazard Communication Standard,
29CFR 1910. 1200. Standard must be consulted for specific requirements.

NFPA rating H-1, F-2, R-0

SECTION 1 -

Manufacturer's Name K & W PRODUCTS

Address 5801 S. EASTERN AVENUE

Emergency Telephone No. 213-720-4680

City, State, and ZIP CITY OF COMMERCE, CA 90040

Other Information Calls

Signature of Person Responsible for Preparation (Optional)

Pat Patu

Date Prepared 11-20-85 (revised 5/12/88)

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY

Hazardous Component(s) (chemical & common name(s))	OSHA PEL	ACGIH TLV	Other Exposure Limits	% (optional)	CAS NO.
Lubricating Base Oil		5,000	(oil mist)		64742-65-0
Isopropyl		400			67-63-0
Toluene		200			108-88-3
Diacetone Alcohol		50			123-42-2
Xylene		100			1330-20-7

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	180°F	Specific Gravity (H ₂ O=1)	0.9	Vapor Pressure (mm Hg)	33.0
	Heavier than air	Vapor Density (Air = 1)			
Solubility in Water	Slightly	Reactivity in Water	N/A		
Appearance and Odor	Light green color liquid with solvent odor.	Melting Point	N/A		

SECTION 4 - FIRE & EXPLOSION DATA

Flash Point	450 F. 70C.	Method Used	TCC	Flammable Limits in Air % by Volume	LEL Lower 2.5	UEL Upper	
Auto-Ignition Temperature	N/A	Extinguisher Media	Regular foam or carbon dioxide or dry chemical				
Special Fire Fighting Procedures	Self contained breathing apparatus with a full face piece.						

Unusual Fire and Explosion Hazards Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors or other ignition sources at locations distant from material handling point.

SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)

Stability Unstable Conditions
Stable to Avoid

Incompatibility (Materials to Avoid) Contact with strong oxidizing agent

Hazardous Decomposition Products Carbon dioxide and/or carbon monoxide, etc.

Hazardous Polymerization May Occur Conditions
Will Not Occur to Avoid

SECTION 6 - HEALTH HAZARDS

1. Acute 2. Chronic

Signs and Symptoms of Exposure Nasal and respiratory irritation, redness in eyes, defatting.

Medical Conditions Generally Aggravated by Exposure Redness, dizziness, weakness, fatigue, nausea, vomiting, diarrhea, headache.

Chemical Listed as Carcinogen or Potential Carcinogen National Toxicology Program Yes No I.A.R.C. Monographs Yes No OSHA Yes No

Emergency and First Aid Procedures

- ROUTES OF ENTRY**
- 1. Inhalation Remove individual to fresh air.
 - 2. Eyes Wash with large amount of water. Get medical attention.
 - 3. Skin Thoroughly wash exposed area with soap and water.
 - 4. Ingestion Do not induce vomiting. Get immediate medical attention.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage Store in cool dry place and away from source of ignition.

Other Precautions Use and store this product with adequate ventilation. Avoid breathing of vapors and prevent repeated or prolonged skin contact. Keep away from children.

Steps to be Taken in Case Material is Released or Spilled Eliminate all sources of ignition and absorb liquid on floor absorbant.

Waste Disposal Methods (Consult federal, state, and local regulations) Dispose in accordance with governmental regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Respiratory Protection (Specify Type) Self contained breathing apparatus.

Ventilation Local Exhaust Local Mechanical (General) Special Other

Protective Gloves Rubber or plastic gloves Eye Protection Chemical splash goggles

Other Protective Clothing or Equipment Impermeable clothing

Work/Hygienic Practices Avoid breathing of vapors and skin contact.

IMPORTANT
Do not leave any blank spaces. If required information is unavailable, unknown, or does not apply, so indicate.