



000140

CARQUESTAF 30

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: CARQUESTAF 30

CARQUEST DIST CENTER
 CARQUEST CORPORATION
 RALEIGH DIST CENTER
 P O BOX 26006

RALEIGH NC 27611

ATTN: PLANT MGR / SAFETY DIR.

08 70 000 0813566-089

PRODUCT: 52025330
 INVOICE: 072353
 INVOICE DATE: 09/21/90
 TO: 2635 HILLBROOK ROAD

Data Sheet No: 0163802-005
 Prepared: 04/24/90
 Supersedes: 10/17/88

SECTION II - PRODUCT IDENTIFICATION

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

DOT Hazard Classification: NOT APPLICABLE

SECTION III - COMPONENTS

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION. SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT	% (by WT)	PEL	TLV	Note
DETERGENT/DISPERSANT ENGINE OIL PACKAGE	10-15			(1)
PETROLEUM LUBE OIL CAS #: 64742-65-0	85-100	5 MG/M3	5 MG/M3	(2)

Notes:

- (1) THIS PRODUCT CONTAINS A MAXIMUM OF 30% ZINC COMPOUNDS. ZINCCOMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III
- (2) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM.

SECTION IV - PHYSICAL DATA

Boiling Point	for COMPONENT(85-100%)	> 425.00 Deg F (218.33 Deg C) @ 760.00 mm Hg
Vapor Pressure	NOT APPLICABLE	
Specific Vapor Density		HEAVIER THAN AIR
Specific Gravity		.891 @ 60.00 Deg F (15.55 Deg C)
Percent Volatiles	NOT APPLICABLE	
Evaporation Rate		SLOWER THAN ETHER
Appearance		CLEAR AND BRIGHT
State		LIQUID
Form		HOMOG SOLN

SECTION V - FIRE AND EXPLOSION INFORMATION

FLASH POINT > 400.0 Deg F (204.4 Deg C)

EXPLOSIVE LIMIT UNAVAILABLE

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.
 WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES: HEALTH- 1 FLAMMABILITY- 1 REACTIVITY- 0

SECTION VI - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.

EFFECTS OF ACUTE OVEREXPOSURE: FOR COMPONENT

TOXICOLOGICAL TESTING INDICATES THAT SIMILIAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR 1910.1200).



000140

CARQUESTAF 30

Page: 2

~~SECTION V - HEALTH HAZARD DATA (Continued)~~FIRST AID:

IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE.

IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM AND QUIET, AND GET MEDICAL ATTENTION.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

~~SECTION VI - REACTIVITY DATA~~

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH: , STRONG OXIDIZING AGENTS.

~~SECTION VII - SPILL OR LEAK PROCEDURES~~STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

LARGE SPILL: PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURRED.

PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

WASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DESTROY BY LIQUID INCINERATION.

DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

~~SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED~~

RESPIRATORY PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

VENTILATION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

PROTECTIVE GLOVES: NOT NORMALLY REQUIRED.

EYE PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

~~SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS~~

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

~~SECTION X - LABEL INFORMATION~~

TOXICOLOGICAL TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA 29 CFR 1910.1200 OR FHSA 16 CFR 1500.

HANDLING & STORAGE:

DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR MORE DETAILED INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS. 24-HOUR EMERGENCY NUMBER 1-800-ASHLAND.

FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

CHRONIC INFORMATION:

CONTAINS: PETROLEUM OIL

*** COMPONENTS APPEAR IN SECTION II ***