


MATERIAL SAFETY DATA SHEET

(513) 860-4949

 MSDS No.: BB0235
 Effective Date: January 1, 2007

SECTION I	NAME	24 HOUR EMERGENCY ASSISTANCE							
Product	n-Butyl Alcohol	 <p>NFPA</p> <p>HAZARD RATING MINIMAL SLIGHT MODERATE SERIOUS SEVERE 0 1 2 3 4</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Health</td><td>2</td></tr> <tr><td>Fire</td><td>3</td></tr> <tr><td>Reactivity</td><td>1</td></tr> </table> <p>HMIS *</p>	Health	2	Fire	3	Reactivity	1
Health	2								
Fire	3								
Reactivity	1								
Chemical Synonyms	Normal Butyl Alcohol; 1-Butanol								
Formula	CH ₃ (CH ₂) ₃ OH								
Unit Size	up to 20 Lt.								
C.A.S. No.	71-36-3								

SECTION II INGREDIENTS OF MIXTURES		
Principal Component(s)	%	TLV Units
n-Butyl alcohol	100%	See Section V.
WARNING! FLAMMABLE! HARMFUL IF SWALLOWED.		
VAPOR HARMFUL. CAUSES SKIN AND EYE IRRITATION.		

SECTION III PHYSICAL DATA			
Melting Point (°F)	-89°C (-128°F)	Specific Gravity (H ₂ O = 1)	0.8108 at 20/20°C.
Boiling Point (°F)	117.5°C (242°F)	Percent Volatile by Volume (%)	100%
Vapor Pressure (mm Hg)	4.1 mm at 20°C	Evaporation Rate (n-Butyl acetate =1)	0.43
Vapor Density (Air=1)	2.6		
Solubility in Water	Moderate.		
Appearance & Odor	Colorless, mobile liquid; strong odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA							
Flash Point (Method Used)	98°F (37°C) TCC.	Flammable Limits in Air % by Volume	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%;">Lower</th> <th style="width: 50%;">Upper</th> </tr> <tr> <td>1.4</td> <td>11.2</td> </tr> </table>	Lower	Upper	1.4	11.2
Lower	Upper						
1.4	11.2						
Extinguisher Media	Carbon dioxide; dry chemical; "alcohol" foam; water fog.						

SPECIAL FIREFIGHTING PROCEDURES

In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

(2004 EMERGENCY RESPONSE GUIDEBOOK, RSPA P 5800.7, GUIDE PAGE NO. 129)

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire or excessive heat may produce hazardous decomposition products; can react vigorously with oxidizing materials. Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure build up which could result in container rupture.

D.O.T. Butanols, 3, UN1120, PG III, Ltd Qty ≤ 5 Lt.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20

SECTION V HEALTH HAZARD DATA BB0235

Threshold Limited Value STEL: 50 ppm (ACGIH 2001). Acute Dermal LD50 4.2g/kg (Rabbit). Toxicity: Acute oral LD50 2.5g/kg (Rat); Acute Inhalation LC50 No deaths at 8000 ppm/4H (Rat).

Effects of Overexposure **INHALATION:** Vapors cause irritation to upper respiratory tract. High vapor concentrations can produce headache, dizziness, drowsiness, CNS depression. **EYES:** Contact with the liquid or vapor causes irritation. Prolonged and repeated exposure to the vapor may result in corneal injury. **SKIN:** Prolonged and repeated contact causes drying and cracking of the skin, which result in skin irritation and dermatitis. **INGESTION:** Harmful if swallowed. May cause central nervous system depression, headache, dizziness and nausea. Target organs: Central nervous system, liver, kidneys.

Emergency and First Aid Procedures **INGESTION:** Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person. **EYES:** Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention. **SKIN:** Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention. **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION VI REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	
		X
Incompatibility (Materials to Avoid)	Strong mineral acids, strong oxidizers, copper and it's alloys. Aluminum containers.	

Hazardous Decomposition Products Thermal decomposition or burning may produce carbon monoxide and unidentified organic compounds.

Hazardous Polymerization	Conditions to Avoid	
	May Occur	Will Not Occur
		X

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Wearing proper protective equipment, provide adequate ventilation. Eliminate all sources of ignition. Absorb in sand, earth or vermiculite. Carefully sweep up and remove. Flush spill area with water. Do not allow wash water to pollute water ways and streams

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only. Dispose of in an approved incinerator or contract with a licensed waste disposal service.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) In the laboratory, work in ventilation hood. Use an approved all purpose organic vapor canister mask for emergency clean up of spills, or an atmosphere-supplying respirator.

Ventilation	Local Exhaust	Recommended.	Special	No.
	Mechanical (General)	Recommended.	Other	No.

Protective Gloves **Eye Protection**

Other Protective Equipment Goggles, smock, apron, proper gloves, ventilation hood, fire extinguisher, eye wash station.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Keep away from heat, sparks, flame. Do not store in copper or its alloys. Wash thoroughly after handling. Do not store in aluminum equipment at temperatures over 120°F. Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals. For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors. Use with adequate ventilation. Remove and wash contaminated clothing.

Revision No. 7 | Date 01/01/07 | Approved James A. Bertsch | Chemical Safety Coordinator JAB

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.