

PRODUCTS CORPORATION

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

STRUCTURE YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY.

NAME: **NO. "7" COOLING SYSTEM FAST FLUSH 2212N**
TYPE: **LIQUID**
APPLICATION: **RADIATOR CLEANER**

03-Dec-85

SIGNAL WORD—CAUTION!

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

CHEMICAL HAZARD RATING

HEALTH=2(MODERATE)

FIRE=0(LEAST)

REACTIVITY=0(LEAST)

**29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS
CAS REGISTRY NO. MATERIAL DESCRIPTION**

7778-53-2 TRIPOTASSIUM PHOSPHATE

9036-19-5 POLYETHYLENE GLYCOL OCTYLPHENYL ETHER

PHYSICAL DATA

GENERAL APPEARANCE: OPAQUE YELLOW LIQUID

ODOR: SLIGHT

PH: 11.2-11.4

FLASH POINT, TCC: 212 F+

ACUTE HEALTH HAZARD DATA

SKIN ABSORPTION: NO HAZARDS KNOWN TO BORDEN.

INGESTION: MAY BE HARMFUL IF SWALLOWED.

INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR
MAY CAUSE IRRITATION OF NOSE, THROAT AND LUNGS.

SKIN: SLIGHTLY TO MODERATELY IRRITATING (PRIMARY SKIN
IRRITATION INDEX LESS THAN 5.0/8.0) WHEN TESTED AS
DESCRIBED IN 16 CFR PART 1500.41.

EYES: SLIGHTLY IRRITATING WHEN TESTED AS DESCRIBED IN 16
CFR PART 1500.42.

HANDLING PRECAUTIONS

INHALATION: AVOID PROLONGED OR REPEATED BREATHING OR
VAPOR.

SKIN: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

EYES: AVOID PROLONGED OR REPEATED CONTACT WITH EYES.
WASH THOROUGHLY AFTER HANDLING.

EMERGENCY AND FIRST AID PROCEDURES

INTERNAL: IF SWALLOWED, DO NOT INDUCE VOMITING. GIVE
LARGE QUANTITIES OF WATER. CALL A PHYSICIAN IMMEDIATELY.
NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION: REMOVE TO FRESH AIR.

SKIN CONTACT: IN CASE OF IRRITATION, FLUSH WITH WATER.

EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION
PERSISTS, CALL A PHYSICIAN.

FIRE AND EXPLOSION HAZARD DATA

WILL NOT BURN UNLESS WATER HAS EVAPORATED.

IN CASE OF FIRE, USE WATER SPRAY, DRY CHEMICAL, FOAM OR
CO₂. USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704-12 (4-3.1).

SPECIAL PROTECTION INFORMATION

NO SPECIAL PROTECTION NECESSARY, HOWEVER WEARING SAFETY
GLASSES, SAFETY SHOES, HARD HATS AND SUITABLE CLOTHING IS
STANDARD PRACTICE IN MANY INDUSTRIAL OPERATIONS.

SPILL OR LEAK PROCEDURES

SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A
CHEMICAL DISPOSAL AREA.

PREVENT ENTRY INTO NATURAL BODIES OF WATER.

WASTE DISPOSAL METHOD

RECOVER FREE LIQUID. ABSORB RESIDUE AND DISPOSE OF
ACCORDING TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.

STORAGE PRECAUTIONS

KEEP CONTAINER CLOSED.

STORE IN A COOL, DRY PLACE.

DOT CLASSIFICATION

NOT REGULATED.

DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ARMOR ALL, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Armor All to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.
