

# MATERIAL SAFETY DATA SHEET



## I PRODUCT IDENTIFICATION

Manufacturer's Name   PENNZOIL CO., GUMOUT DIVISION		CAS Number: MIXTURE	
Address   710 GATEWAY CENTER #4 PITTSBURGH, PENNSYLVANIA 15222-1469		MSDS Code: 000624	
Emergency Telephone No.   (713) 236-6070		<b>NFPA Hazard Identification</b> Degree of Hazard      Hazard Ratings Health: 1              0 - Least 1 - Slight Fire: 2                    2 - Moderate Reactivity: 0            3 - High 4 - Extreme	
Trade Name   GUMOUT® GAS TREATMENT		# 7599	
Synonyms   TUNEUP TREATMENT; PETROLEUM HYDROCARBON			

## II INGREDIENTS

COMPONENT NAME CAS NUMBER	HAZARDOUS IN BLEND	PERCENTAGE		COMPONENT EXPOSURE LIMITS		UNITS
		MIN	MAX			
STODDARD SOLVENT 8052-41-3	YES	90.00	95.00	OSHA PEL TWA	525.0000	MG/M3
AMINE POLYMER TRADE SECRET	NO	10.00		ACGIH TLV TWA	525.0000	MG/M3
				OSHA PEL		NO LIMIT
				ACGIH TLV		NO LIMIT

BY: ENVIRONMENTAL, SAFETY & HEALTH (713) 546-8512      EFFECTIVE DATE: JULY 20, 1990

### DISCLAIMER OF WARRANTY:

THE INFORMATION CONTAINED HEREIN IS BASED UPON DATA AVAILABLE TO US, AND REFLECTS OUR BEST PROFESSIONAL JUDGEMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT, SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.

REQUIRED UNDER USDL SAFETY AND HEALTH REGULATIONS FOR SHIP REPAIRING, SHIPBUILDING, AND SHIPBREAKING (29 CFR 1915, 1916, 1917).