

# Material Safety Data Sheet



Date of issue 17 May 2011  
Version 12.01

## 1. Product and company identification

**Product name** : PERFORMANCE + GLAMOUR CLEARCOAT  
**Code** : D8152  
**Supplier** : PPG Industries, Inc.  
One PPG Place,  
Pittsburgh, PA 15272  
**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
01-800-00-21-400 (Mexico)  
**Technical Phone Number** : 1-800-647-6050

## 2. Hazards identification

**Emergency overview** : DANGER!  
FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED. ASPIRATION HAZARD. CAN ENTER LUNGS AND CAUSE DAMAGE. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.  
Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep away from heat. Do not smoke. Do not swallow. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

### Potential acute health effects

**Inhalation** : May be harmful if inhaled. Irritating to respiratory system. Can irritate eyes, nose, mouth and throat.  
**Ingestion** : May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.  
**Skin** : Harmful in contact with skin. Irritating to skin.  
**Eyes** : Irritating to eyes.

### Over-exposure signs/symptoms

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone.

**Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See toxicological information (Section 11)

### 3. Composition/information on ingredients

| <u>Name</u>                                     | <u>CAS number</u> | <u>%</u> |
|-------------------------------------------------|-------------------|----------|
| xylene                                          | 1330-20-7         | 10 - 30  |
| 2-methoxy-1-methylethyl acetate                 | 108-65-6          | 3 - 7    |
| Acetone                                         | 67-64-1           | 3 - 7    |
| ethylbenzene                                    | 100-41-4          | 1 - 5    |
| heptan-2-one                                    | 110-43-0          | 1 - 5    |
| 2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol | 25973-55-1        | 0.1 - 1  |
| acrylic acid, monoester with propane-1,2-diol   | 25584-83-2        | 0.1 - 1  |
| Styrene                                         | 100-42-5          | 0.1 - 1  |
| Methyl methacrylate                             | 80-62-6           | 0.1 - 1  |
| Toluene                                         | 108-88-3          | 0.1 - 1  |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### 5. Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

#### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Vapors are heavier than air and may spread along floors. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120F / 49C.

## 8. Exposure controls/personal protection

| Name                            | Result | ACGIH           | OSHA            | Ontario | Mexico          | PPG             |
|---------------------------------|--------|-----------------|-----------------|---------|-----------------|-----------------|
| xylene                          | TWA    | 100 ppm         | 100 ppm         | 100 ppm | 100 ppm         | Not established |
|                                 | STEL   | 150 ppm         | Not established | 150 ppm | 150 ppm         | Not established |
| 2-methoxy-1-methylethyl acetate | TWA    | Not established | Not established | 50 ppm  | Not established | Not established |

**8 . Exposure controls/personal protection**

|                     |      |                 |                            |                 |                 |                 |
|---------------------|------|-----------------|----------------------------|-----------------|-----------------|-----------------|
| Acetone             | TWA  | 500 ppm         | 1000 ppm                   | 500 ppm         | 1000 ppm        | Not established |
|                     | STEL | 750 ppm         | Not established            | 750 ppm         | 1260 ppm        | Not established |
| ethylbenzene        | TWA  | 100 ppm         | 100 ppm                    | 100 ppm         | 100 ppm         | Not established |
|                     | STEL | 125 ppm         | Not established            | 125 ppm         | 125 ppm         | Not established |
| heptan-2-one        | TWA  | 50 ppm          | 100 ppm                    | 25 ppm          | 50 ppm          | Not established |
|                     | STEL | Not established | Not established            | Not established | 100 ppm         | Not established |
| Styrene             | TWA  | 20 ppm S        | 100 ppm Z                  | 35 ppm          | 50 ppm S        | Not established |
|                     | STEL | 40 ppm S        | 600 ppm Z A<br>200 ppm Z C | 100 ppm         | 100 ppm S       | Not established |
| Methyl methacrylate | TWA  | 50 ppm SS       | 100 ppm                    | 50 ppm SS       | 100 ppm         | Not established |
|                     | STEL | 100 ppm SS      | Not established            | 100 ppm SS      | 125 ppm         | Not established |
| Toluene             | TWA  | 20 ppm          | 200 ppm Z                  | 20 ppm          | 50 ppm S        | Not established |
|                     | STEL | Not established | 500 ppm Z A<br>300 ppm Z C | Not established | Not established | Not established |

**Key to abbreviations**

A = Acceptable Maximum Peak  
 ACGIH = American Conference of Governmental Industrial Hygienists.  
 C = Ceiling Limit  
 F = Fume  
 IPEL = Internal Permissible Exposure Limit  
 OSHA = Occupational Safety and Health Administration.  
 R = Respirable  
 Z = OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

S = Potential skin absorption  
 SR = Respiratory sensitization  
 SS = Skin sensitization  
 STEL = Short term Exposure limit values  
 TD = Total dust  
 TLV = Threshold Limit Value  
 TWA = Time Weighted Average

**Consult local authorities for acceptable exposure limits.**

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Personal protection**

**Eyes** : Safety glasses with side shields.  
**Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

## 8 . Exposure controls/personal protection

- Respiratory** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: 6.67°C (44°F)
- Explosion limits** : Lower: 2.1%
- Color** : Not available.
- Odor** : Not available.
- pH** : Not available.
- Boiling/condensation point** : >37.78°C (>100°F)
- Melting/freezing point** : Not available.
- Specific gravity** : 0.97
- Density ( lbs / gal )** : 8.1
- Vapor pressure** : 6.3 kPa (47.5 mm Hg) [20°C]
- Vapor density** : Not available.
- Volatility** : 54% (v/v), 47.83% (w/w)
- Evaporation rate** : 176 (butyl acetate = 1)
- Partition coefficient: n-octanol/water** : Not available.
- % Solid. (w/w)** : 52.17

## 10 . Stability and reactivity

- Stability** : Stable under recommended storage and handling conditions (see section 7).
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials, strong acids, strong alkalis
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11 . Toxicological information

### Acute toxicity

| Product/ingredient name         | Result                | Species | Dose       | Exposure |
|---------------------------------|-----------------------|---------|------------|----------|
| xylene                          | LD50 Oral             | Rat     | 4.3 g/kg   | -        |
|                                 | LD50 Dermal           | Rabbit  | >1.7 g/kg  | -        |
|                                 | LC50 Inhalation Vapor | Rat     | 5000 ppm   | 4 hours  |
| 2-methoxy-1-methylethyl acetate | LD50 Oral             | Rat     | 8532 mg/kg | -        |
|                                 | LD50 Dermal           | Rabbit  | >5 g/kg    | -        |
| Acetone                         | LD50 Oral             | Rat     | 1.8 g/kg   | -        |

## 11 . Toxicological information

|                                                 |                       |        |             |         |
|-------------------------------------------------|-----------------------|--------|-------------|---------|
| ethylbenzene                                    | LD50 Dermal           | Rabbit | 20 g/kg     | -       |
|                                                 | LC50 Inhalation Vapor | Rat    | 76000 mg/m3 | 4 hours |
|                                                 | LD50 Oral             | Rat    | 3.5 g/kg    | -       |
|                                                 | LD50 Dermal           | Rabbit | >5000 mg/kg | -       |
|                                                 | LC50 Inhalation Vapor | Rat    | 4000 ppm    | 4 hours |
| heptan-2-one                                    | LD50 Oral             | Rat    | 1.6 g/kg    | -       |
|                                                 | LD50 Dermal           | Rabbit | 10.206 g/kg | -       |
|                                                 | LD50 Oral             | Rat    | >2325 mg/kg | -       |
| 2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol |                       |        |             |         |
| acrylic acid, monoester with propane-1,2-diol   | LD50 Dermal           | Rabbit | 0.17 g/kg   | -       |
| Styrene                                         | LD50 Oral             | Rat    | 1 g/kg      | -       |
|                                                 | LC50 Inhalation Vapor | Rat    | 2700 ppm    | 4 hours |
|                                                 | LD50 Oral             | Rat    | 7872 mg/kg  | -       |
| Methyl methacrylate                             | LD50 Dermal           | Rabbit | >5 g/kg     | -       |
|                                                 | LC50 Inhalation Vapor | Rat    | 78000 mg/m3 | 4 hours |
|                                                 | LD50 Oral             | Rat    | 636 mg/kg   | -       |
| Toluene                                         | LD50 Dermal           | Rabbit | 8.39 g/kg   | -       |
|                                                 | LC50 Inhalation       | Rat    | 49 g/m3     | 4 hours |

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Defatting irritant

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

### Target organs

: Contains material which causes damage to the following organs: brain, central nervous system (CNS).  
Contains material which may cause damage to the following organs: blood, kidneys, liver, peripheral nervous system, gastrointestinal tract, upper respiratory tract, skin, eye, lens or cornea, nose/sinuses, throat.

### Carcinogenicity

**Carcinogenicity** : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

### Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|------|
| xylene                  | A4    | 3    | -   | -     | -   | -    |
| Acetone                 | A4    | -    | -   | -     | -   | -    |
| ethylbenzene            | A3    | 2B   | -   | -     | -   | -    |
| Styrene                 | A4    | 2B   | -   | -     | -   | -    |
| Methyl methacrylate     | A4    | 3    | -   | -     | -   | -    |
| Toluene                 | A4    | 3    | -   | -     | -   | -    |

**Teratogenicity** : Contains material which may cause birth defects, based on animal data.

**Developmental effects** : Contains material which may cause developmental abnormalities, based on animal data.

**Fertility effects** : Contains material which may impair male fertility, based on animal data. Contains material which may impair female fertility, based on animal data.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------|---------|----------|
|                         |        |         |          |

## 12 . Ecological information

|                     |                                              |                                                            |          |
|---------------------|----------------------------------------------|------------------------------------------------------------|----------|
| xylene              | Acute LC50 3300 to 4093 ug/L Fresh water     | Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss | 96 hours |
| Acetone             | Acute LC50 >100000 ug/L Fresh water          | Fish - Fathead minnow - Pimephales promelas                | 96 hours |
|                     | Acute LC50 10000 ug/L Fresh water            | Daphnia - Water flea - Daphnia magna                       | 48 hours |
|                     | Acute EC50 7200000 ug/L Fresh water          | Algae - Green algae - Selenastrum sp.                      | 96 hours |
| ethylbenzene        | Acute LC50 4200 ug/L Fresh water             | Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss | 96 hours |
|                     | Acute LC50 5100 to 5700 ug/L Marine water    | Fish - Atlantic silverside - Menidia menidia               | 96 hours |
|                     | Acute EC50 2930 to 4400 ug/L Fresh water     | Daphnia - Water flea - Daphnia magna                       | 48 hours |
|                     | Chronic NOEC 3300 ug/L Marine water          | Fish - Atlantic silverside - Menidia menidia               | 96 hours |
|                     | Chronic NOEC 6800 ug/L Fresh water           | Daphnia - Water flea - Daphnia magna                       | 48 hours |
| heptan-2-one        | Acute LC50 131000 to 137000 ug/L Fresh water | Fish - Fathead minnow - Pimephales promelas                | 96 hours |
| Styrene             | Acute LC50 4020 to 4990 ug/L Fresh water     | Fish - Fathead minnow - Pimephales promelas                | 96 hours |
|                     | Acute LC50 9.1 to 16 ppm Marine water        | Fish - Sheepshead minnow - Cyprinodon variegatus           | 96 hours |
|                     | Acute EC50 4700 to 7400 ug/L Fresh water     | Daphnia - Water flea - Daphnia magna                       | 48 hours |
|                     | Chronic NOEC 4000 ug/L Fresh water           | Fish - Fathead minnow - Pimephales promelas                | 96 hours |
|                     | Chronic NOEC 5.1 to 16000 ppm Marine water   | Fish - Sheepshead minnow - Cyprinodon variegatus           | 96 hours |
|                     | Chronic NOEC 1900 ug/L Fresh water           | Daphnia - Water flea - Daphnia magna                       | 48 hours |
| Methyl methacrylate | Acute LC50 130000 ug/L Fresh water           | Fish - Fathead minnow - Pimephales promelas                | 96 hours |
| Toluene             | Acute LC50 5800 ug/L Fresh water             | Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss | 96 hours |
|                     | Acute EC50 6000 ug/L Fresh water             | Daphnia - Water flea - Daphnia magna                       | 48 hours |
|                     | Chronic NOEC 28000 ug/L Fresh water          | Daphnia - Water flea - Daphnia magna                       | 48 hours |

## 13 . Disposal considerations

### Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14 . Transport information

| Regulation | UN number | Proper shipping name | Classes | PG* | Additional information |
|------------|-----------|----------------------|---------|-----|------------------------|
| UN         | 1263      | PAINT                | 3       | II  | -                      |
| IMDG       | 1263      | PAINT                | 3       | II  | -                      |
| DOT        | 1263      | PAINT                | 3       | II  | -                      |

PG\* : Packing group

Reportable quantity RQ : CERCLA: Hazardous substances.: 4-methylpentan-2-one: 5000 lbs. (2270 kg); Acetone: 5000 lbs. (2270 kg); Toluene: 1000 lbs. (454 kg); Methyl methacrylate: 1000 lbs. (454 kg); Styrene: 1000 lbs. (454 kg); ethylbenzene: 1000 lbs. (454 kg); xylene: 100 lbs. (45.4 kg);

## 15 . Regulatory information

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Australia inventory (AICS)** : This product contains a component which may restrict import to the notifier and/or to other parties holding a concurrent notification or agreement.

**Canada inventory (DSL)** : All components are listed or exempted.

**China inventory (IECSC)** : All components are listed or exempted.

**Europe inventory (REACH)** : Please contact your supplier for information on the inventory status of this material.

**Japan inventory (ENCS)** : At least one component is not listed.

**Korea inventory (KECI)** : Not determined.

**New Zealand (NZIoC)** : Not determined.

**Philippines inventory (PICCS)** : Not determined.

### United States

#### U.S. Federal regulations :

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** heptan-2-one; Acetone; ethylbenzene; xylene; 2-methoxy-1-methylethyl acetate

CERCLA: Hazardous substances.: 4-methylpentan-2-one: 5000 lbs. (2270 kg); Acetone: 5000 lbs. (2270 kg); Toluene: 1000 lbs. (454 kg); Methyl methacrylate: 1000 lbs. (454 kg); Styrene: 1000 lbs. (454 kg); ethylbenzene: 1000 lbs. (454 kg); xylene: 100 lbs. (45.4 kg);

### SARA 311/312 MSDS Distribution - Chemical Inventory - Hazard Identification:

| Chemical name | CAS # | Acute | Chronic | Fire | Reactive | Pressure |
|---------------|-------|-------|---------|------|----------|----------|
|---------------|-------|-------|---------|------|----------|----------|

## 15. Regulatory information

|                                                 |            |   |   |   |   |   |
|-------------------------------------------------|------------|---|---|---|---|---|
| xylene                                          | 1330-20-7  | Y | N | Y | N | N |
| 2-methoxy-1-methylethyl acetate                 | 108-65-6   | Y | N | Y | N | N |
| Acetone                                         | 67-64-1    | Y | N | Y | N | N |
| ethylbenzene                                    | 100-41-4   | Y | Y | Y | N | N |
| heptan-2-one                                    | 110-43-0   | Y | N | Y | N | N |
| 2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol | 25973-55-1 | N | Y | N | N | N |
| acrylic acid, monoester with propane-1,2-diol   | 25584-83-2 | Y | Y | N | Y | N |
| Styrene                                         | 100-42-5   | Y | Y | Y | Y | N |
| Methyl methacrylate                             | 80-62-6    | Y | Y | Y | Y | N |
| Toluene                                         | 108-88-3   | Y | Y | Y | N | N |
| Product as-supplied :                           |            | Y | Y | Y | N | N |

| SARA 313              | <u>Chemical name</u> | <u>CAS number</u> | <u>Concentration</u> |
|-----------------------|----------------------|-------------------|----------------------|
| Supplier notification | : xylene             | 1330-20-7         | 10 - 30              |
|                       | ethylbenzene         | 100-41-4          | 1 - 5                |
|                       | Styrene              | 100-42-5          | 0.1 - 1              |

**Additional environmental information** is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### Canada

**WHMIS (Canada)** : Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

### Mexico

#### Classification

Flammability : 3    Health : 2    Reactivity : 0

## 16. Other information

### Hazardous Material Information System (U.S.A.)

Health : 2    \*    Flammability : 3    Physical hazards : 0  
 (\*) - Chronic effects

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)

Health : 2    Flammability : 3    Instability : 0

Date of previous issue : 3/29/2011.

Organization that prepared : EHS  
 the MSDS

☑ Indicates information that has changed from previously issued version.

### Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.