

SAFETY-KLEEN 105 PARTS WASHING SOLVENT

MATERIAL SAFETY DATA SHEET



SECTION I -- PRODUCT INFORMATION

Safety-Kleen Corporation - 777 Big Timber Road - Elgin, IL 60123
 For Product/Sales Information Call 708/697-8460

| <i>EMERGENCY TELEPHONE</i> | <i>MEDICAL:</i> | <i>TRANSPORTATION:</i> |
|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------|
| These numbers are for emergency use only. If you desire non-emergency information about this product, please call the telephone number listed above. | 800/942-5969 or 312/942-5969 RUSH POISON CONTROL CENTER CHICAGO, ILLINOIS (24 HOURS) | 800/424-9300 CHEMTREC |

IDENTITY (TRADE NAME): SAFETY-KLEEN 105 PARTS WASHING SOLVENT

SYNONYMS: PETROLEUM DISTILLATES, PETROLEUM NAPHTHA, MINERAL SPIRITS, STODDARD SOLVENT

SK PART NUMBER: 6617

FAMILY/CHEMICAL NAME: HYDROCARBON SOLVENT

PRODUCT USAGE: SOLVENT FOR CLEANING AND DEGREASING PARTS

SECTION II -- HAZARDOUS COMPONENTS

| NAME | SYNONYM | % | CAS NO. | OSHA PBL (ppm) | ACGIH TLV (ppm) |
|------------------------------------------------------------------------|-----------------|--------------------|-------------------------|---------------------------|---------------------------|
| Parts Washer Solvent (consists predominantly of C9-C13 hydrocarbon) | Mineral Spirits | (Typical % by Wt.) | | | |
| C9-C13 Saturated Hydrocarbon | | 85 | 64741-41-9 ² | 100 (Stoddard Solvent) | 100 (Stoddard Solvent) |
| *Toluene | | 0.5 | 108-88-3 ✓ | 100 150 STEL | 100 150 STEL |
| *Xylene | | 1.0 | 1330-20-7 ✓ | 100 150 STEL | 100 150 STEL |
| *Ethyl Benzene | | 0.5 | 100-41-4 ✓ | 100 Skin 125 STEL | 100 125 STEL |
| C8+ Aromatics | | 12.0 | Mixture | N/E | N/E |
| Chlorinated Solvents | | (Max 1% by Wt.) | | | |
| *1,1,1 Trichloroethane | | <0.5 | 71-55-6 ✓ | 350 450 STEL | 350 450 STEL |
| *Tetrachloroethylene | | <0.5 | 127-18-4 ✓ | 25 | 50 200 STEL |

N/E = Not Established
 * See Section X - Other Regulatory Information

SECTION III -- PHYSICAL DATA

PHYSICAL STATE, APPEARANCE AND ODOR: Combustible liquid - clear, green, with characteristic hydrocarbon odor.

BOILING POINT: 300° - 429° F

EVAPORATION RATE: (Butyl Acetate = 1) 0.1
PERCENT VOLATILE: 99.9%
VAPOR DENSITY: 4.9 (Air = 1)
VAPOR PRESSURE: 2 mm of Hg at 68° F
SOLUBILITY IN WATER: Negligible
pH: Not Applicable
SPECIFIC GRAVITY: 0.77 to 0.80
MOLECULAR WEIGHT: Approximately 142
VOLATILE ORGANIC COMPOUNDS: 795 g/L

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 105° F (SETA)
AUTOIGNITION TEMPERATURE: 473° F
CONDITIONS OF FLAMMABILITY: Materials must be moderately heated before ignition can occur.
FLAMMABLE LIMITS IN AIR - LOWER: 0.7% **UPPER:** 6.0%
EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical, water (mist only).
FIRE FIGHTING PROCEDURES -- SPECIAL: NFPA 704 Rating 2-2-0

Keep storage tanks cool with water spray. Use self-contained breathing apparatus (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be toxic. Heated tanks may rupture, explode or be thrown into the air. Vapors are heavier than air and may travel great distances to ignition source and flashback.

HAZARDOUS COMBUSTION PRODUCTS:

Thermal decomposition and burning may produce carbon monoxide.

SECTION V -- REACTIVITY DATA

STABILITY: Normally stable even under fire exposure conditions and is not reactive with water. Normal firefighting procedures may be used.
INCOMPATIBILITY (CONDITIONS TO AVOID): Strong oxidizing agents (e.g. chlorine, peroxides, strong acids).
HAZARDOUS POLYMERIZATION: Not known to occur under normal conditions.
HAZARDOUS DECOMPOSITION PRODUCTS: Normally none; however, incomplete burning may yield carbon monoxide.

SECTION VI -- HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Skin and eye contact; inhalation.

HEALTH HAZARD DATA/SIGNS AND SYMPTOMS OF EXPOSURE:

ACUTE: *Skin:* Prolonged or repeated contact tends to remove skin oils, possibly leading to irritation and dermatitis. No significant skin absorption hazard.

Eyes: Contact may cause slight to moderate irritation. High vapor concentrations (> 500 ppm) are irritating to the eyes.

Inhalation: High concentrations of vapor or mist may be irritating to the respiratory tract, cause headaches, dizziness, nausea, impaired coordination, anesthesia and may have other central nervous system effects.

Ingestion: Low order of acute oral toxicity. May cause irritation of the throat, nausea, vomiting and symptoms of central nervous system depression. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

CHRONIC: Prolonged and/or repeated contact may cause drying and cracking of the skin or dermatitis.

OTHER POTENTIAL HEALTH HAZARDS:

The impurities that may be present are not expected to add significantly to the effects of exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Individuals with pre-existing central nervous system dysfunction may have increased susceptibility to the effects of exposure. Contact with skin may aggravate pre-existing dermatitis.

CARCINOGENICITY: Tetrachloroethylene is listed by IARC and NTP as a suspected carcinogen. Studies indicate that Ethyl Benzene and 1,1,1 Trichloroethane are experimental teratogens.

SECTION VII -- EMERGENCY AND FIRST AID PROCEDURES

- EYES:** For direct contact, flush eyes with water for 15 minutes lifting upper and lower lids occasionally. Consult physician if irritation or pain persists. If irritation or redness from exposure to vapors or mists develop, move victim away from exposure into fresh air.
- SKIN:** Remove contaminated clothing. Wash skin twice with soap and water. If irritation develops and persists, consult a physician.
- INGESTION:** If conscious, dilute with 4 to 8 ounces of water and seek immediate medical attention. DO NOT induce vomiting.
- INHALATION:** Remove to fresh air immediately. Use oxygen if there is difficulty breathing or artificial respiration if respiration has stopped. Do not leave victim unattended. Seek immediate medical attention if necessary.

SECTION VIII -- PRECAUTIONS FOR SAFE USE AND HANDLING

- SPILL PROCEDURES:** Remove all ignition sources. Ventilate area and avoid breathing vapors. For large spills, isolate area and deny entry. If possible, contain as a liquid for possible re-refining. Absorb onto sand or other absorbent material. Shovel into closable container for disposal. Wear protective equipment specified below. Contain away from surface waters and sewers.
- WASTE DISPOSAL METHODS:** Dispose in accordance with Federal, State, and local regulations. Contact Safety-Kleen regarding recycling.
- HANDLING PRECAUTIONS:** Avoid contact with eyes, skin or clothing. Use in well ventilated area and avoid breathing vapors or mists. Keep away from heat, sparks and open flames.
- SHIPPING AND STORING PRECAUTIONS:** Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, grind or expose containers to flame or other sources of ignition. Keep container tightly closed when not in use and during transport.

**PERSONAL
HYGIENE:**

Use good personal hygiene. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco products. Launder contaminated clothing and clean protective equipment before reuse.

SECTION IX -- CONTROL MEASURES

VENTILATION:

Provide local exhaust or general dilution ventilation as determined necessary to maintain concentrations of vapors or mists below applicable exposure limits. Where explosive mixtures may be present, systems safe for such locations should be used.

**PROTECTIVE
GLOVES:**

Use nitrile or neoprene gloves to prevent contact with skin.

EYE

PROTECTION:

Where there is likelihood of spill or splash, wear chemical goggles or faceshield. Contact lenses should not be worn.

**RESPIRATORY
PROTECTION:**

Use NIOSH-approved respiratory protective equipment when concentration of vapors or mists exceeds applicable exposure limit. Depending on the airborne concentration, use a respirator or gas mask with appropriate cartridges and canisters (for organic vapor with mist prefilter). A self-contained breathing apparatus (SCBA) is required for large spills and emergencies. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134 - Respiratory Protection.

**OTHER PROTECTIVE
EQUIPMENT:**

Wear solvent-resistant boots, apron or other protective clothing where spills and splashes are possible. A source of clean water should be available in work areas for flushing the eyes and skin.

SECTION X -- OTHER REGULATORY INFORMATION

DOT PROPER SHIPPING NAME: Petroleum Naphtha

DOT CLASS: Combustible Liquid

DOT NUMBER: UN 1255

SARA TITLE III: Product contains a toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. Toxic constituents are listed with an asterisk in Section II of this Material Safety Data Sheet.

Product poses the following physical and/or health hazard(s) as defined in 40 CFR 370.3 (Sections 311, 312 of SARA Title III):

Immediate (Acute) Health Hazard
Delayed (Chronic) Health Hazard
Fire Hazard

SECTION XI -- PREPARATION INFORMATION

PREPARED BY: SK Product Review Committee

FORM NO. 900-14-001

ORIGINAL ISSUE DATE: July 20, 1989 **REVISED:** March 12, 1990 **SUPERSEDES:** July 20, 1989

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature, are made hereunder with respect to information or the product to which information refers. The data contained on this sheet applies to the material as supplied to the user.