



000691

IGLOO/DP R-12 *P/N 90014*

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: IGLOO/DP R-12
 CAS NUMBER: 75-71-8

CARQUEST DIST CTR-RALEIG
 P.O. BOX 26006
 2635 MILLBROOK RD

RALEIGH NC 27611
 ATTN: PLANT MGR / SAFETY DIR.

08 70 000 1505400-000

PRODUCT: 80011001
 INVOICE: 115161
 INVOICE DATE: 09/05/89
 TO:

Data Sheet No: 0016534-005
 Prepared: 08/21/89
 Supersedes: 08/14/89

SECTION II - PRODUCT IDENTIFICATION

General or Generic ID: HALOGENATED HYDROCARBON
 DOT Hazard Classification: NON-FLAMMABLE COMPRESSED GAS (173.300)

SECTION III - COMPONENTS

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION. SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT	% (by WT)	PEL	TLV	Note
DICHLORODIFLUORO METHANE CAS #: 75-71-8	>95	1000 PPM	1000 PPM	

SECTION IV - PHYSICAL DATA

Boiling Point	for PRODUCT	-21.60 Deg F -29.77 Deg C 760.00 mm Hg
Vapor Pressure	for PRODUCT	4700.00 mm Hg 77.00 Deg F 25.00 Deg C
Specific Vapor Density	AIR = 1	4.3
Specific Gravity		1.310 77.00 Deg F 25.00 Deg C
Percent Volatiles		100.00%
Evaporation Rate		FASTER THAN ETHER
Appearance		CLEAR & COLORLESS
State		GAS
Form		HOMOGENEOUS SOLUTION

SECTION V - FIRE AND EXPLOSION INFORMATION

FLASH POINT NOT APPLICABLE
 EXPLOSIVE LIMIT NOT APPLICABLE
 EXTINGUISHING MEDIA:
 HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS: , HYDROGEN CHLORIDE, PHOSGENE, HYDROGEN FLUORIDE, ETC
 FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.
 SPECIAL FIRE & EXPLOSION HAZARDS: NOT APPLICABLE
 NFPA CODES: HEALTH- 1 FLAMMABILITY- 0 REACTIVITY- 1

SECTION VI - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL 1000 PPM
 THRESHOLD LIMIT VALUE 1000 PPM

EFFECTS OF ACUTE OVEREXPOSURE: FOR PRODUCT

EYES - CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.
 SKIN - CONTACT WITH LIQUID CAN RESULT IN FREEZING OF TISSUE.
 BREATHING - EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS, AND EVEN DEATH.
 SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

FIRST AID:

IF ON SKIN: SLOWLY WARM THE AFFECTED AREA WITH TEPID WATER. GET MEDICAL ATTENTION.
 IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.



000691

IGLOO/DP R-12

Page: 7

~~SECTION V - HEALTH HAZARD DATA (Continued)~~

IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM AND QUIET, AND GET MEDICAL ATTENTION.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

DO NOT GIVE STIMULANTS. EPINEPHRINE OR EPHEDRINE MAY ADVERSELY AFFECT THE HEART WITH FATAL RESULTS.

PRIMARY ROUTE(S) OF ENTRY:

INHALATION, SKIN CONTACT

~~SECTION VI - REACTIVITY DATA~~

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH: , ALKALI METALS, POWDERED METALS, ALKALINE METALS

~~SECTION VII - SPILL OR LEAK PROCEDURES~~STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: VENTILATE AREA.

ALLOW TO EVAPORATE.

LARGE SPILL: ALLOW TO EVAPORATE. PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA UNTIL LEAK HAS BEEN REPAIRED.

WASTE DISPOSAL METHOD:

SMALL SPILL: ALLOW MATERIAL TO EVAPORATE.

LARGE SPILL: RETURN TO SUPPLIER FOR RECLAMATION.

~~SECTION VIII - PERSONNEL PROTECTIVE EQUIPMENT TO BE USED~~

RESPIRATORY PROTECTION: IF WORKPLACE EXPOSURE LIMIT(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II), A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS: , POLYVINYL ALCOHOL

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER)

OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

~~SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS~~

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.